

VA2014wm

50CM / 20" Widescreen LCD

WITH 20,000:1 DYNAMIC CONTRAST RATIO

Budget-friendly, widescreen performance

ViewSonic's 50cm/20" VA2014wm LCD brings value to big, widescreen displays. This display doesn't compromise on features with 1600x900 resolution for brilliant HD images. This stylish 50cm/20-inch LCD delivers extreme clarity, amazing colour with 20,000:1 dynamic contrast ratio and fast ClearMotiv® 5ms video response. Benefit from greater productivity with the ability to view two fullsize documents side-by-side or work in multiple applications simultaneously on the widescreen display. Integrated speakers in a stylish, slim-bezel design provide multimedia enjoyment. Eco-mode conserves power and can extend backlight life. VA2014wm fits seamlessly into any office décor. It's great for desktop applications at home, school or in the office.



- > **Widescreen aspect ratio**
The widescreen aspect ratio allows you to view high resolution content in its native format with no stretching or distortion.
- > **20000:1 Dynamic Contrast Ratio**
Provides darker black levels and better overall front-of-screen performance.
- > **ClearMotiv® 5ms video response time**
Fast 5ms video response enables digital HD broadcast-quality video.
- > **1600 x 900 resolution**
The 1600 x 900 resolution allows PC movies and games to be viewed without losing any detail, or huge spreadsheets and multiple applications side-by-side for increased productivity.
- > **ECO Mode**
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
- > **Aspect ratio adjustment**
Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

VA2014wm

50CM/20" Widescreen LCD

ViewSonic®
See the difference™ 

Model No.VS13388



| | | | |
|-------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| LCD | Size | 50CM/20" wide Color TFT Active Matrix LCD 16:9 aspect ratio | |
| | Display Area | 443 x 249 (mm) | |
| | Optimum Resolution | 1600×900 | |
| | Brightness | 250 cd/m ² (typ.) | |
| | Contrast Ratio | 1000:1 (typ.) / 20000:1 dynamic | |
| | Viewing Angles | 170° (H), 160° (V) at 10:1 c/r, 170°(H) 170°(V) at 5:1 c/r | |
| | Response Time | 5ms (typ.) | |
| | Pixel Pitch | 0.276mm(H) x 0.276mm(V) | |
| | Panel Surface | Anti-Glare, Hard coating (3H) | |
| | Light Source | 50,000 hrs (typ.) | |
| Colour Support | 16.7 M (6-bits + Hi FRC) | | |
| INPUT | Analogue | RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) | |
| | Sync | Separate Sync | |
| | Frequency | Fh: 24-82kHz, Fv: 50-75Hz | |
| COMPATIBILITY | PC | VGA up to 1600×900 Non Interlaced | |
| | Mac | Power Mac, up to 1600×900 | |
| CONNECTOR | Analogue | 1×15 pin mini D-sub | |
| | Audio | 1×3.5 mm Audio in | |
| | Power | Built-in power Adapter, 3-Pin plug | |
| AUDIO | Speaker | 2W×2 | |
| POWER | Voltage | AC 100-240V (Universal); 50/60Hz(Switch) | |
| | Consumption | 25 (typ) | |
| | Eco Mode | optimize 23W (typ.) / conserve 19W (typ.) | |
| | Save mode | ≤ 0.5W | |
| ERGONOMICS | Tilt | 20° ~ -5° | |
| CONTROLS | Basic | [1], [2], Power, Down[▼], Up[▲] | |
| | OnView | Auto Image Adjust | |
| | | Contrast/Brightness | |
| | | Audio adjust: Volume mute | |
| | | Colour Adjust: sRGB, 9300K, 7500K, 6500K, 5000K | |
| | | User Colour : [R, G, B] | |
| | | Information | |
| | | Manual Image Adjust:H/V position, horizontal size, fine tune, sharpness, dynamic contrast, aspect ratio, Eco mode, setup menu, language select, resolution notice, OSD Position, OSD Time Out, OSD Background, memory recall. | |
| | OPERATING | Temperature | 41°F - 95°F (5°C - 35°C) |
| | CONDITIONS | Humidity | 20 - 80% (Non condensed) |
| DIMENSIONS | Physical (w/ stand) | 481 x 369 x 200 (mm), 18.94 x 14.51 x 7.86 (in) | |
| | (WXHXD) | Physical (w/o stand) | 481 x 288 x 64(mm), 18.94 x 11.32 x 2.52 (in) |
| WEIGHT | Net | 4 kg (8.8 lbs) | |
| | Gross Weight | 5.8 kg (12.8 lbs) | |
| REGULATIONS | | CB,WEEE,ROHS, EAEPT, UL/cUL, FCC-B, IRAM, NOM, Energy Star, ERGO,CE, Ukraine, GOST-R+Hygienic ,SASO, BSMI, PSB, C-TICK, KCC, CCC | |
| WALL MOUNT | | VESA 100mm x 100mm | |
| POWER MANAGEMENT | | ENERGY STAR | |
| PACKAGE CONTENTS | | LCD display, VGA cable, Power cable, Quick Start Guide, ViewSonic ,Wizard CD | |

Rev.1c



BZ02

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.
Copyright © 2008 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies.
VSE 2010/07/19 V1

For more product information, visit us on the web at viewsoniceurope.com