

Optimize Desktop Performance with WLED Backlight Technology

Dramatically improved picture quality can now be yours... with ViewSonic's VX1932wm-LED monitor. DCR reaches mega values for true-to-life image depth and clarity and the LED backlight automatically detects the signal level and intelligently controls backlight brightness – allowing blacks to be truly black and whites to be whiter in a bright environment. Grey levels are also enhanced through the intelligent control circuits, yielding superb grey scale performance. Along with all of the image quality improvements, the power consumption is reduced by as much as 50% with no compromises on visual performance, and the LED backlight is eco-friendly with mercury free technology.

VX1932wm-LED

**19"VIEWABLE
LED BACKLIGHT LCD**

WITH 10,000,000:1 DYNAMIC CONTRAST RATIO



- > **Mega dynamic contrast ratio**
Provides darker black levels and better overall front-of-screen performance.
- > **ENERGY STAR qualified**
50% less power consumption, 15.5W(typ.) with Energy Star 5.0 certification.
- > **ECO mode**
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life. Windows7 & Vista Premium certification.
- > **Full 19"viewable widescreen with 1440x900 resolution**
- > **Dual input DVI-D/D-sub data input.**
- > **2W x 2 integrated speakers**
- > **Windows7 & Vista Premium certification.**
- > **Aspect ratio adjustment**
Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.
- > **ClearMotiv® 5ms video response time**
Ultra-fast 5ms video response enables digital HD broadcast-quality video.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic
See the difference™ 

VX1932wm-LED

ViewSonic®
See the difference™ 

19" VIEWABLE LED BACKLIGHT LCD

Model No. VS11444



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	19" wide Color TFT Active Matrix LCD
	Display Area	474mm(H)×296mm(V) / 18.6in(H)×11.6in(V)
	Optimum Resolution	1440 x 900
	Brightness	250 cd/m2 (typ.)
	Contrast Ratio	1000:1 (typ.)
	Dynamic Contrast Ratio	1,000,000:1 (Mega)
	Viewing Angles	170° (H), 160° (V) (CR≥10)
	Response Time	5 ms (G to G)
	Pixel Pitch	0.282 mm(H) x 0.282 mm(V)
	Panel Surface	Anti-glare
Light Source Life	30,000 (typ.) (White LED)	
VIDEO INPUT	Analogue	RGB Analogue (75 ohms, 0.7 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
COMPATIBILITY	Sync	H/V Separated, Composite, Sync On Green(TTL)
	Frequency	Fh: 24 – 82 kHz, Fv: 50 – 75 Hz
CONNECTORS	PC	VGA up to 1440x900 Non Interlaced
	MAC	Power Mac (up to 1440x900)
	Analogue	15 pin mini D-sub x 1
	Digital	DVI-D x 1
AUDIO	Speaker	2W x 2
POWER	Voltage	100-240VAC; 50/60 Hz
	Consumption	15.5 W (typ.) / 19.5 W (max)
ERGONOMICS	Tilt	20 ~ -5 degrees
CONTROLS	Basic	[1], [2], Soft power button, Up[▲], Down[▼]
	Main Menu	Auto Image Adjust, Contrast/Brightness, Input Select, Color Adjust (sRGB, 9300K, 6500K, 5400K, User Color [R, G, B]), Information, Manual Image Adjust (Horizontal Size, H/V Position, Fine Tune, Sharpness, Aspect Ratio, ECO Mode), Setup Menu (Language Select, Resolution Notice, OSD Position, OSD Time Out, OSD), Background, Memory Recall
OPERATING	Temperature	0°C - 40°C (32°F - 104°F)
CONDITION	Humidity	20% to 80% (no condensation)
DIMENSIONS	Physical (mm)	450 mm x 434 mm x 209 mm
		(W x H x D)
WEIGHT	Net	4.7 Kg (10.3 lbs)
REGULATIONS		Energy Star 5.0, CCC, RoHS, China Energy, BSMI, CB, PSB, KCC (MIC), SASO, CE, C-tick, TCO 5.0
Wall Mount		Meet VESA (100mm x 100mm) Standards
PACKAGE	Contents	Power Cable, VGA Cable, DVI Cable, Audio Cable,

ViewSonic Europe Limited/UK

Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom
Tel: +44 (0)207 382 8250
Fax: +44 (0)207 382 8251

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

5 rue de Helder
75009 Paris
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. 2010/01/20 V2

For more product information, visit us on the web at viewsoniceurope.com