

# VX2753mh-LED

27" 1ms Super-Slim Full HD LED Monitor

## Go LED Go Green



ViewSonic's VX2753mh-LED features an LED backlight 27" ultra-thin widescreen monitor with up to 40% energy savings compared to a regular 27" monitor. Environmentally friendly mercury free VX2753mh-LED offers Full HD 1920x1080 resolution, two HDMI inputs, external power supply, 1ms response time, 30,000,000:1 MEGA dynamic contrast ratio, book stand option and SRS Premium Sound. Ideal for both home and office with a glossy black finish. The aspect ratio adjustment feature automatically senses the input single and will not stretch a 4:3 signal but instead will position the image in the middle of the screen with side bars.

The industry's best pixel performance policy, energy saving Eco-mode and Windows 7 certification, make VX2753mh-LED a great long term investment.

- > Uses 40% less power  
Without compromising your viewing quality and has eco-friendly mercury free WLED backlight.
- > Full HD 1080p with 16:9 aspect ratio  
Achieves perfect image reproduction without distortion.
- > 2 HDMI inputs plus VGA input for diverse connectivity
- > Integrated speakers with SRS Premium Sound for multimedia applications
- > Dynamic contrast ratio at 30,000,000:1  
For true-to-life picture depth and clarity in any room.
- > PC and Mac<sup>®</sup> compatible
- > Book stand option

Model No.	VX2753mh-LED	
LCD	Size Optimum Resolution Brightness Contrast Ratio Dynamic Contrast Ratio Viewing Angle Response Time Pixel Pitch Panel Surface Color Support	27" wide Color TFT Active Matrix LCD with 16:9 aspect ratio 1920 x 1080 300 cd/m2 (Typ.) 1200 :1 (Typ.) 800:1(min) 30,000,000:1 170° (H), 160° (V) 3.4 (Typ), GTG : 1 ms 0.3114 mm (H) x 0.3114mm (V) Anti-Glare, Hard coating (3H) 16.7 M
INPUT	Analogue Sync Frequency	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p) Separate Sync / Composite Sync / SOG Fh = 24 – 83 kHz ; Fv = 50 ~ 76 Hz
COMPATIBILITY	PC Mac	VGA up to 1920x1080 non-interlaced Power Mac, up to 1920x1080
CONNECTOR	Analogue Digital Audio Power	1×15 pin mini D-sub HDMI x 2 (HDMI ver.1.3) Audio Out - 3.5 mm jack (blue) / Audio In - 3.5 mm jack (green) External Power Adapter
SPEAKER POWER	Speaker Voltage Consumption Save mode ECO mode	2W x2 AC 100-240V (Universal); 50 / 60Hz(Switch) 31W (typ.) w/o Audi, 44w(Max) with Audio ≤1w 26W (Optimize) / 21W (Conserve)
OPERATING CONDITIONS	Temperature Humidity	32° F-104° F (0°C-40° C) 20-90% (no condensation)
DIMENSIONS	Physical (w/stand)	658 mm (W) x 480 mm (H) x 212 mm (D)
WEIGHT	Net (w/stand)	4.7kg
REGULATIONS		BSMI, CCC, China Energy, PSB, C-Tick, KCC, CE, CB, GostR/Hygienic, Ukraine, UL/cUL, FCC-B, ICES-B, ENERGY STAR 5.0, EPEAT Silver, WEEE, RoH