

The VG2732m-LED is one of ViewSonic's latest 27" models. It's 27" display with a native 1920x1080 resolution. What makes it even more appealing is the LED backlight for up to 50% energy savings. The Monitor is also fully ergonomic with 90° pivot, height adjust, swivel and tilt. The VG2732m-LED has a slim matt bezel design coupled with hidden stereo speakers. You can put it on your desk or mount on your wall or on any VESA® compliant monitor stand ideal for monitor applications and usage. With ViewSonic's strongest pixel performance guarantee and 3-year limited warranty, you will have peace of mind in your investment





## Widescreen aspect ration with 1920 x 1080 resolution

Full HD 1080p resolution delivers stunning image quality with superior detail and sharpness for home and business applications. Ideal for graphic design, video production, and advanced business applications requiring professional monitor performance.





## Planet-Friendly Mercury-Free LED Backlighting

WLED backlighting enhances display performance, delivering an outstanding colour range, and adjusts contrast ratios for remarkably detailed images. ViewSonic's ecofriendly, mercury-free LED backlighting further conserves up to 25% more energy when compared to conventional displays.

#### **Sleek Frameless Bezel Design**

The distinctive and stylish ViewSonic's VG2732m-LED fuses a frameless bezel design into simple black glossy design, to provide users a seamless display.

# OptiSync® digital/analog inputs expand your connectivity

Multi-mode input technology supports both digital (DisplayPort + DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.



4-port USB hub provides easy connectivity for USB devices.



# Multi-functional base design (pivot, height adjustment, swivel)

VESA compliant wall-mount interface and detachable base for ergonomic flexibility with  $90^{\circ}$  pivot, 135cm height, tilt and 356° swivel adjustments.



#### **Eco-mode**

ViewSonic's proprietary Eco-mode function is built into all LED displays, offering options to "Optimize (75%)" or "Conserve (50%)". Both modes reduce display brightness and conserve energy by up to 50%. Especially in low ambient light, Eco-mode adjusts brightness and improves visibility while reducing eye fatigue and prolonging the display's lamp life. With Eco-mode, your lamp replacement and energy expenditures will be reduced, making it an eco-friendly choice.



#### **Dual integrated stereo speakers**

The ViewSonic VG2732m-LED has two integrated 2W stereo speakers for enhanced multimedia performance with crystal-clear stereo sound.

Rendimiento del pixel	Monitores LED
ISO9241-3: 2008 Standard	2 Brillo 2 Oscuro 5 Total
Garantía ViewSonic Pixel	2 Brillo 2 Oscuro 3 Total

## Rendimiento del pixel garantizado + Garantia limitada a 3 anos

Uno de los aspectos que convierten a ViewSonic en líder de mercado de soluciones de visualización es su dedicación a la calidad. ViewSonic se compromete a utilizar los paneles de más alta calidad y ofrece un rendimiento de pixel líder de la industria.

### **Technical Specifications**

	Área de visualización	23.6" (597.89mm) horizontal x 13.3" (336.31mm) vertical ; 27 diagonal
	Resolución óptima	1920x1080
	Tiempo de respuesta	3.4ms (typ)
	Fuente de luz	Long life, 30,000 hrs. (typ)
Superficie de	Superficie del panel	panel Anti-Glare
	Tamaño del píxel	
	Tamaño	
	Brillo	300 cd/m² (typ)
	Soporte de color	16.7 M (6-bits + Hi FRC)
Audio	Altavoces	2 x 2 Watt
COMPATIBILIDAD	PC	VGA up to 1920x1080 non-interlaced
	Mac®	Power Mac™ up to 1920x1080
Dimensiones	Embalaje	28.7" x 20.6" x 9.5" (729mm x 523mm x 240mm)
	Físicas con la base	25.3" x 17.0" x 9.5" (642mm x 434mm x 241mm)
	Físicas sin la base	25.3" x 15.4" x 2.6" (642mm x 391mm x 65mm)
Normativas		CB, WEEE, RoHS, UL/cUL, FCC-B, IRAM, NOM, EPEAT-Silver, BSMI, PSB, C-TICK, CCC, CEL, CECP, CU, UkrSEPRO, TCO, EnergyStar
CONTENIDO DE LA CAJA		LCD monitor, Power cable, Audio Cable, USB Cable, VGA Cable Quick Start Guide, ViewSonic Wizard CD-ROM
Entrada	Syncronización	H/V Separated
	Frecuencia	Fh: 24-82kHz, Fv: 50-75Hz
Conectividad	Digital	DisplayPort and DVI-D
	Analógico	15-pin mini D-sub
	USB	1-up / 4-down
	Audio	3.5 mm Audio in
	Alimentación	Built-in power adapter, 3-Pin plug
Alimentación	Modo Eco	Optimize: 26W / Conserve: 22W
	Voltaje	AC 100–240V (Universal); 50/60Hz(Switch)
	Consumo	Standard: 29W
VESA® MONTAJE		VESA 100mmx100mm
ERGONOMÍA	Giratoria	Right 178º / Left 178º

	Ajuste de altura	0~135cm
	Pivote	0~90º (Clockwise)
	Inclinación	$20^{\circ} \sim -5^{\circ}$
Peso	Neto sin base	11.5 lb. (5.2 kg)
	Bruto	20.3 lb. (9.2 kg)
	Neto con base	14.5 lb. (6.6 kg)
CONDICIONES DE		
FUNCIONAMIENTO	Temperatura	32-104° F (0-40° C)
	Humedad	20–90% (non-condensing)

### **ViewSonic® Limited Warranty**

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

#### For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.