CD3200

32" COMMERCIAL **LCD DISPLAY**

Get your message across, brilliantly

ViewSonic's 32" CD3200 Commercial Display is designed for use in educational, retail, public and commercial signage applications. This widescreen LCD ACCOMMODATES MIXED MEDIA CONTENT with enough room for movies, internet content, digital pictures, PowerPoint, Flash files and much more. Wide viewing angles, high brightness and contrast and 1366 x 768 native resolution display crystal clear images in virtually any room lighting while the fast 8ms response time delivers fast-action video. MULTIPLE INPUTS INCLUDING HDMI, S-video, component, composite and PC VGA, give you plenty of connectivity options for all your digital signage needs.



With ViewSonic displays, you'll always be in time.

HIGH DEFINITION DIGITAL SIGNAGE

- > Vivid graphics, clear text, stunning video Ultra-high brightness of 500cd/m² (typ.), high contrast ratio of 1200:1 (typ.), and 1366 x 768 optimum PC resolution provides vibrant video and crisp data images on the desktop or in the living room.
- > Expand your options with plug-and-play connectivity and universal remote control This HDTV-ready, LCD provides the ultimate viewing experience with plug-and-play, high-end connectivity for other HD devices and content.
- > OptiSync® technology featuring HDMI Add versatility to your LCD with support for HDMI with highdefinition content protection (HDCP) and analogue (VGA) signals, plus component, S-video, composite, and video input.
- > Optional stand and speakers Installation options include wall or counter mount. Add audio to you video content with optional speakers.
- > Complete digital signage solution Add an NMP-530 Network Media Player and choose scheduling software from Best Wave to implement a complete digital signage solution.



AND SERVICES







CD3200

32" COMMERCIAL LCD DISPLAY



Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 Tel: +358 20 7120 860

Tel: +971 (0) 4 88 11 871



ViewSonic displays with the right information – getting you there on time

Complete Your Digital
Signage Solution

Add a ViewSonic® NMP-530 Network Media Player



Choose a scheduling software



Recommended for 1–25 display installations. Visit BestWave.com for more details.

OPTIONAL ACCESSORIES

> Stand STND-008 > Speakers SPK-007







ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Туре	32" colour TFT active matrix, wide XGA 1366 x 768
	Display Area	69.8cm (horizontal) x 39.2cm (vertical), 81.3cm diagonal
	Native Resolution	1366 x 768
	Contrast Ratio	1200:1 (typ.)
	Viewing Angles	176° horizontal, 176° vertical
	Response Time	8ms (grey-to-grey typ.)
	Brightness	500cd/m² (typ.)
	Aspect Ratio	16:9
	Glass Surface	Anti-glare, hard coating (3H)
INPUT	PC	RGB analogue (75 ohms, 0.7 Vp-p), RS232 (control), USB (FW update)
	TV	1 x composite, 1 x component YPbPr/YCbCr, 1 x S-video
	Audio	3.5mm mini stereo audio in/out and RCA (left/right) audio in
	Digital	HDMI (with HDCP and audio support)
	Tuner	None
AUDIO OUTPUT	Speakers	2 x 10-watt (optional)
INPUT SIGNAL	Video	RGB analogue (0.7 Vp-p, 75 ohm), PAL, SECAM, NTSC, SDTV/EDTV (480i/p, 576i/p), HDTV (720p, 1080i)
CONNECTOR	Analogue	1 x 15-pin mini D-Sub (detachable cable)
	Digital	1 x HDMI (with HDCP)
	Component	1 x RCA set (YPbPr/YCbCr)
	S-Video	1 x 4-pin mini DIN jack (Y/C)
	Composite	1 x RCA (CVBS)
	Control	1 x D-sub RS-232
	USB	1 x USB Typ B (for firmware update)
	Audio	1 x 3.5mm mini stereo audio in
		2 x RCA (left/right) audio in
		3 x RCA (left/right/subwoofer) audio line out
		1 x SP/DIF (optic) HDMI loop through
		2 x speaker connector (for optional speakers)
	Power	3-pin plug
POWER	Voltage	AC 100–240V (universal), 50/60Hz
	Consumption	< 220watt (typ.)
CONTROLS	Basic	Power, channel +/-, volume +/-, menu, source, exit/wide
	PC Mode	Auto sync, contrast, brightness, H/V position, colour
		, late eyine, contract, singilaricos, i.i, v position, corear
		temperature, aspect ratio control (ARC), OSD language,
	AV Mode	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour
	AV Mode	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance
	AV Mode	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all
OPERATING	AV Mode Temperature	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC,
CONDITIONS	Temperature Humidity	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing)
CONDITIONS DIMENSIONS	Temperature Humidity W x H x D (mm)	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing) 965 x 582 x 108 (without stand)
CONDITIONS	Temperature Humidity W x H x D (mm) Net	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing) 965 x 582 x 108 (without stand) 22.2kg (without stand)
CONDITIONS DIMENSIONS WEIGHT	Temperature Humidity W x H x D (mm)	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C–40°C 10–85% (non-condensing) 965 x 582 x 108 (without stand) 22.2kg (without stand) 33.0kg (without stand)
CONDITIONS DIMENSIONS WEIGHT WALL MOUNT	Temperature Humidity W x H x D (mm) Net	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing) 965 x 582 x 108 (without stand) 22.2kg (without stand) 33.0kg (without stand) VESA FDMI 100mm x 100mm, 100mm x 200mm
CONDITIONS DIMENSIONS WEIGHT WALL MOUNT REGULATIONS	Temperature Humidity W x H x D (mm) Net Gross	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing) 965 x 582 x 108 (without stand) 22.2kg (without stand) 33.0kg (without stand) VESA FDMI 100mm x 100mm, 100mm x 200mm CE, CB, Gost, UL/cUL, FCC, NOM, WEEE, RoHS
CONDITIONS DIMENSIONS WEIGHT WALL MOUNT	Temperature Humidity W x H x D (mm) Net Gross	temperature, aspect ratio control (ARC), OSD language, reset all, treble, balance Brightness, contrast, colour, hue, sharpness, colour temperature, sound (volume, bass, treble, balance), ARC, OSD language, reset all 0°C-40°C 10-85% (non-condensing) 965 x 582 x 108 (without stand) 22.2kg (without stand) 33.0kg (without stand) VESA FDMI 100mm x 100mm, 100mm x 200mm

ViewSonic Europe Limited/UK	ViewSonic Germany	ViewSonic France	ViewSonic Corporation	ViewSonic Belux
Riverside House	Hanns-Martin-Schleyer-Straße 18A	Parc des Barbanniers	381 Brea Canyon Road	ViewSonic Denmar
7th Floor	47877 Willich	1 allée des Bas Tilliers	Walnut	ViewSonic Finland
2a Southwark Bridge Road	Germany	92230 Gennevilliers	California 91789-0708	ViewSonic MEA

London, SE1 9HA USA ViewSonic Netherlands Tel: +31 (0)20 491 9254 United Kingdom ViewSonic Norway Tel: +47 (0) 22 88 17 60 Tel: +44 (0) 207 921 2200 Tel: +49 (0) 21 54 91 88 0 Tel: +33 (0) 1 41 47 49 00 Tel: +1 909 869 7976 ViewSonic Spain Tel: +34 (0) 91 63 05 339 Fax: +44 (0) 207 921 2201 Fax: +49 (0) 21 54 91 88 10 Fax: +33 (0) 1 41 47 49 10 Fax: +1 909 869 7958 ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

Copyright © 2007, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS CD3200 08/07-UK

¹ HDTV cable provider or satellite provider and set-top box needed to view HDTV. ² May require optional Mac adapter.