

Versatile flagship projector

The ViewSonic® PJ1173 delivers maximum impact for large-venue presentations. With 5200 LUMENS and 1000:1 contrast ratio (typ.), this PREMIUM PROJECTOR with optional lenses is ideally suited for larger conference rooms, lecture halls, religious institutions and boardrooms. The PJ1173 is fully-featured with a native XGA 1024 x 768 resolution, advanced image processing, manual lens shift, and horizontal and vertical (auto) keystone correction for perfect images. Network connectivity allows you to REMOTELY CONTROL AND MANAGE THE PROJECTOR and the 4 x 4-watt SRS® WOW STEREO SPEAKERS give your presentations powerful sound. An intelligent built-in movement detector will lock the projector if its position is changed and thereby guard against theft and unauthorised use. The PJ1173 is the fully-featured choice for the most demanding presentation situations and smooth video entertainment in large venues.

PJ1173

**HIGH BRIGHTNESS
MULTIMEDIA PROJECTOR**

WITH OPTIONAL LENSES



SRS (O) **WOW**

RAISING THE BAR ON YOUR PRESENTATIONS

- > **Ultimate video source flexibility**
Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display or enjoy pure digital loss-free images by connecting via HDMI.
- > **Network control through RJ-45 and RS232**
Manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.
- > **Enhanced security features**
Next to the standard PIN lock and a robust security bar the PJ1173 comes with an intelligent position detector which will deter theft by locking the device upon change of its position.
- > **The perfect image in any setting**
Digital horizontal and vertical (auto) keystone correction, manual lens shift, and optical zoom ensure the perfect image in any room.
- > **Superior 16-watt stereo sound**
Four stereo speakers with SRS® WOW technology for panoramic 3D sound.
- > **Easy maintenance**
Easy top and side access to lamp and filter covers saves time and money when replacing these spare parts.
- > **Optional lenses make installation flexible**
Four easy-to-install bayonet lens options allow you to project in rooms at virtually any distance.



ViewSonic®
See the difference™ 

PJ1173



HIGH BRIGHTNESS MULTIMEDIA PROJECTOR WITH OPTIONAL LENSES



Screen size [inch (m)]	4:3 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	0.9 (35)	1.1 (42)	5 (2)	41 (16)
60 (1.5)	1.8 (71)	2.2 (86)	9 (4)	82 (32)
80 (2.0)	2.4 (96)	2.9 (115)	12 (5)	110 (43)
100 (2.5)	3.0 (120)	3.7 (144)	15 (6)	137 (54)
200 (5.1)	6.1 (241)	7.4 (291)	30 (12)	274 (108)
300 (7.6)	9.2 (363)	11.1 (437)	46 (18)	411 (162)
350 (8.9)	10.8 (424)	13.0 (510)	53 (21)	480 (189)

Screen size [inch (m)]	16:9 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	1.0 (38)	1.2 (46)	-1 (0)	39 (15)
60 (1.5)	2.0 (78)	2.4 (94)	-2 (-1)	77 (30)
80 (2.0)	2.6 (104)	3.2 (126)	-3 (-1)	103 (41)
100 (2.5)	3.3 (131)	4.0 (157)	-4 (-2)	129 (51)
200 (5.1)	6.7 (263)	8.0 (317)	-8 (-3)	257 (101)
300 (7.6)	10.0 (395)	12.1 (476)	-12 (-5)	386 (152)
350 (8.9)	11.7 (462)	14.1 (556)	-15 (-6)	450 (177)

OPTIONAL ACCESSORIES

- > Replacement lamp RLC-038
- > Universal ceiling mount kit WMK-018
- > Fixed short throw Lens, throw ratio: 0.8:1 LEN-003
- > Short throw lens, throw ratio: 1.2:1 - 2.0:1 LEN-004
- > Long throw lens, throw ratio: 2.0:1 - 3.9:1 LEN-005
- > Ultra long throw Lens, throw ratio: 3.9:1 - 7.4:1 LEN-006



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

PROJECTOR	Type	3 x 0.8" Poly-Si TFT with Micro Lens
	Resolution	1024 x 768 XGA native, (max. 1600 x 1200 UXGA compressed)
	Lens	Manual zoom, manual focus, manual lens shift
	Zoom Factor	1.2 (F = 1.7-1.9/f = 24.3mm-29.2mm)
	Digital Keystone	Vertical ± 40°, horizontal ± 20°
DISPLAY	Size	30"-350" (0.76m-7.62m) (Diagonal)
	Throw Distance	0.9m-13m
	Throw Ratio	1.5-1.8:1
	Lamp	275W UHB, 2000/3000 hours ¹
	Brightness	5200 ANSI lumens (typ.)
	Contrast Ratio	1000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speaker	4 x 4-watt with SRS® WOW technology (virtual surround-sound)
INPUT SIGNAL	Video	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N), SECAM, SD (480i/576i), ED (480p/576p), HD (720p/1080i).
	Frequency	Fh: 31-92kHz; Fv: 56-120Hz
COMPATIBILITY	PC	Analogue: VGA up to UXGA (compressed), 1024 x 768 @ 60Hz preferred
	Mac ^{®**}	Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
CONNECTOR	PC-RGB (in)	2 x 15-pin mini D-sub
	PC-RGB (out)	1 x 15-pin mini D-sub
	RGB-BNC	BNC-5 (x1 set)
	Digital	1 x HDMI 1.3
	Composite Video	1 x RCA jack
	Audio (in)	2 x 3.5mm stereo mini jack (for PC), 2 x RCA set L/R jack (for video)
	Audio (out)	1 x 3.5mm stereo mini jack Integrated into universal digital M1-D connector
	USB	(Type B for mouse control only)
	Control	1 x 9-pin D-sub RS-232
	Network	1 x RJ-45
POWER	Voltage	AC 100-240V, 50/60Hz (auto switch)
	Consumption	460W (<15W in standby)
FUNCTIONS	OSD	Brightness, Contrast, Gamma, Color Temp, Color, Tint, Sharpness, Active Iris, My Memory, Aspect, Over Scan, V position, H position, H Phase, H size, Auto Adjust Execute, Progressive, Video NR, 3D-YCS, Color Space, Component, Video Format, HDMI, Frame Lock, RGB IN, Resolution, Auto Keystone Execute, Keystone V, Keystone H, Whisper, Mirror, Volume, Treble, Bass, SRS WOW, Speaker, Audio, HDMI Audio, Language, Menu Position, Blank, Start up, Myscreen, Myscreen Lock, Message, Source Name, Auto Search, Auto Keystone, Auto On, Auto off, Lamp time, Filter Time, My Button, Service (Fan Speed, Auto Adjust, Ghost, Filter Message, Lens Type, Key Lock, Remote Receive, Remote FREQ., Information, Factory Reset), Security (Security password change, Myscreen password change, PIN Lock, Transition Detector, My Text Password, My Text Display, My Text Writing), Network (DHCP, IP address, Subnet mask, Default gateway, Time difference, Date and time, e-shot, Information, Service)
OPERATING CONDITIONS	Temperature	5°C-35°C
	Humidity	10%-85% (non condensation)
NOISE LEVEL	Normal	35dB (typ.)
	Eco mode	29dB (typ.)
DIMENSIONS	(W x H x D mm)	418 x 139 x 319 (physical) 555 x 244 x 478 (packaging)
WEIGHT	Net	7.1kg
	Gross	11.6kg
REGULATIONS		UL/C-UL, FCC B, UL-DEMKO/GS, CB, CE, C-Tick, NOM, GOST, Hygienic, Ukraine, ROHS, WEEE
PACKAGE CONTENTS		Projector, power cables, VGA cable, AV cable, remote control, batteries, lens cap, Quick Start Guide (12 languages), ViewSonic Wizard CD (User guide) (multi-language)
OTHER FEATURES		Auto off and on, short throw optics, 7 picture modes (Dynamic, Cinema, Normal, Whiteboard, Board [Black/Green], Daylight), full function remote control with laser pointer, magnify & freeze function, progressive scan, 3:2 pull down, advanced video noise filters, overscan correction, digital gamma correction, customizable startup logo/remote buttons and projection settings
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

¹ Running Eco mode exclusively can extend lamp life. ² May require optional Mac adapter.

Copyright © 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ1173 05/08-UK

For more product information, visit us on the web at ViewSonicEurope.com