

# PJ359w

Light, bright and portable projector

## Versatile, portable performance

The ViewSonic® PJ359w ultra-portable projector is a performance leader with a rich feature set at an affordable price. The PJ359w is specially designed to be compatible with widescreen-format laptops and imaging applications. It delivers 2,000 LUMENS AND 1280X800 WXGA RESOLUTION for crisp, detailed images in any lighting situation. Automatic keystone correction ensures your image is perfectly proportioned, while the preset screen modes give you the best possible picture for your projection surface. This impressive, portable projector features HDMI 1.3 connectivity and supports HD signals up to 1080p. It's easy to set up and its DIRECT OFF FEATURE allows you to unplug it and go. The PJ359w is ideal for table-top or mounted use in the office, classroom or on the road.



### OUTSTANDING PRESENTATIONS

- > **Supports HD signals including 720p and 1080i**  
Capable of displaying HD signals as well as other video and data sources.
- > **Multiple color correction modes**  
Blackboard, greenboard and whiteboard modes give you the best possible picture regardless of the projection surface.
- > **Whisper-mode extends lamp life**  
Extend the life of your lamp up to 3,000 hours\*\* and reduce noise output.
- > **Closed captioning**  
Integrated closed captioning decoder for the hearing impaired.
- > **Enhanced security features**  
Assign a PIN code to password protect the projector from unauthorized use.
- > **Off to Go**  
Direct off feature lets you unplug the projector and go.
- > **MyScreen Startup**  
Customize your startup with a company logo or favorite picture using the MyScreen function.



# PJ359w

Light, bright and portable projector

Model No.VS12188



## Optional Accessories

Replacement lamp.....RLC-039

Screen size (diagonal)	16:10 screen						Screen height
	Projection distance						
	Min.		Max.				
inch	m	m	inch	m	inch	cm	inch
30	0.8	0.9	37	1.1	45	40	16
60	1.5	1.9	75	2.3	90	81	32
80	2	2.6	101	3.1	121	108	42
90	2.3	2.9	113	3.5	136	12	48
100	2.5	3.2	126	3.8	151	135	53
120	3	3.8	151	4.6	182	162	64
150	3.8	4.8	189	5.8	228	202	79
200	5.1	6.4	253	7.7	304	269	106
250	6.4	8	316	9.6	380	337	132
300	7.6	9.6	380	11.6	456	404	159

  

Screen size (diagonal)	4:3 screen						Screen height
	Projection distance						
	Min.		Max.				
inch	m	m	inch	m	inch	cm	inch
30	0.8	1.1	42	1.3	51	46	18
60	1.5	2.2	85	2.6	102	91	36
80	2	2.9	114	3.5	137	122	48
90	2.3	3.3	128	3.9	154	137	54
100	2.5	3.6	143	4.4	171	152	60
120	3	4.4	171	5.2	206	183	72
150	3.8	5.4	215	6.5	258	229	90
200	5.1	7.3	286	8.7	344	305	120
250	6.4	9.1	358	10.9	430	381	150
300	7.6	10.9	430	13.1	516	457	180



ISO 9001:2000  
FM 40187



ISO 14001:1996  
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>PROJECTOR</b>	Type	0.59" inches (X3) Poly-Si TFT with Micro Lens	
	Resolution	WXGA 1280X800	
	Lens	Manual zoom/focus (1:1.2X)	
	Support Resolution	1600X1200 (compressed)	
<b>DISPLAY</b>	Keystone	Vertical Digital keystone correction: +/-30 degrees	
	Size	30"-300" (Diagonal)/ 0.8m-7.6m	
	Throw Distance	0.9m-11.6m (35"-456")	
	Throw Ratio	1.5:1 ~ 1.8:1	
	Lamp	190 watt	
	Lamp Life (Normal / Eco Mode)	2000 / 3000 (hours)	
	Brightness	2,000 Lumens	
	Contrast Ratio	500:1	
<b>AUDIO</b>	Speakers	1 x 1w	
	<b>INPUT SIGNAL</b>	RGB	RGB analog
		Video	NTSC, PAL, SECAM
		HDTV Signal	HDTV (480i/p, 576i/p, 720p, 1080i, 1080p)
<b>COMPATIBILITY</b>	Frequency	Fh:31-106 KHz, Fv:56-120 Hz	
	PC	VGA to UXGA	
<b>CONNECTOR</b>	Mac	Up to SXGA (may require Mac Adapter)	
	RGB Input	15-pin D-sub (in x 2)	
<b>POWER</b>	Digital Input	HDMI (x 1)	
	Video Inputs	composite / S-video	
	Audio In-and output	3.5mm Mini Jack (in x1 / out x1) / RCA Jack (in x1)	
	USB	USB type B x 1(for mouse control only)	
	Voltage	100~120VAC/200~240VAC(Auto Switching), 50/60Hz (universal)	
	Consumption	310W (typ)	
	Noise Level Normal / Eco Mode (dB typ.)	44dB (Max.) / 37dB (Max.)	
<b>OPERATING NOISE</b>	<b>LANGUAGE</b>	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Traditional Chinese, Turkish	
		Standby/On, input, menu	
<b>CONTROLS</b>	Basic	Brightness, contrast, gamma, color temp, color, tint, sharpness, My memory, aspect, over scan, V position, H position, H phase, H size, auto adjust execute, progressive, video nr, color space, component, video format, HDMI, frame lock, computer in, resolution, auto keystone execute, keystone, whisper, mirror, standby, volume, audio, HDMI audio, language, menu position, blank, start up, myscreen, Myscreen lock, message, source name, template, auto search, auto keystone, auto on/off, lamp time, filter time, my button, my source, service (fan speed, auto adjust, ghost, filter message, key lock, remote freq., information, factory reset), security (security password change, Myscreen password change, pin lock, transition detector, my text password, my text display, my text writing), cc (display, mode, channel)	
	OSD	Temperature 41°F - 95°F (5°C - 35°C)	
<b>OPERATING CONDITION</b>	Humidity	10% - 85% (non-condensing)	
<b>DIMENSIONS (W x D x H)</b>	Physical	274mm x 205mm x 59mm (without feet)	
		10.79" x 8.07" x 2.32"	
<b>WEIGHT</b>	Net	1.8 Kg (3.96 lb)	
<b>REGULATIONS</b>		UL60950-1/C-UL, FCC B, CE, DEMKO-GS, WEEE, RoHS, C-Tick	

**ViewSonic Europe Limited/UK**  
Tower 42  
25 Old Broad Street  
London EC2N 1HQ  
United Kingdom

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany  
Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France  
Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA  
Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux** Tel: +31 (0)20 491 9254  
**ViewSonic Denmark** Tel: +45 70 22 11 71  
**ViewSonic Finland** Tel: +358 (0)20 7120 860  
**ViewSonic MEA** Tel: +971 (0) 4 88 11 871  
**ViewSonic Norway** Tel: +47 (0) 22 88 17 60  
**ViewSonic Spain** Tel: +34 (0) 91 63 05 339  
**ViewSonic Sweden** Tel: +46 (0) 8 50 71 30 00

\*Requires SRS Audio Sandbox Software to be installed. \*\*Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD6211

For more product information, visit us on the web at [viewsoniceurope.com](http://viewsoniceurope.com)