

## Bright, powerful, video performance

The ViewSonic PJ862 raises the bar for performance. Captivate large audiences with bright crisp images with this full-function multimedia projector that delivers native XGA 1024 x 768 resolution and ultra bright 3100 ANSI lumens. Enjoy greater variety of source material with multiple ports including DVI – HDCP, component and multiple VGA inputs. Ideal for IT managers in enterprise, public sector and medium sized companies who would like to manage a fleet of projectors.

# PJ862

**HIGH BRIGHTNESS NETWORK  
PROJECTOR**  
WITH DIGITAL VIDEO INPUT



### BRIGHT PERFORMER IN ANY SETTING

- > **Bright in virtually any setting with 3100 lumens**  
Packs 3100 lumens in just 4.0kg. It's the bright choice for mobile professionals.
- > **Ultimate video source flexibility**  
Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.
- > **Supports HD signals including 720p and 1080i**  
Capable of displaying HD signals as well as other video and data sources.<sup>1</sup>
- > **Advanced video features**  
Progressive scan for superior video performance.
- > **The perfect image in any setting**  
Use the one-touch setup button and auto vertical keystone correction to set up quickly.
- > **Asset Management Capabilities**  
Control and manage a fleet of projectors via RJ45 and RS232 ports.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# PJ862

## HIGH BRIGHTNESS NETWORK PROJECTOR WITH DIGITAL VIDEO INPUT

**ViewSonic®**   
See the difference™



<b>PROJECTOR</b>	Type	3 x 0.79" Poly-Si TFT active matrix with MLA
	Pixel Format	1024 x 768 XGA native, (max. 1600 x 1200 UXGA compressed)
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2 (F = 1.7 – 2.1 / f = 24.4mm – 29.3mm)
	Digital Keystone	Vertical ± 15°, horizontal ± 15°
<b>DISPLAY</b>	Size	30" – 300" (0.76m – 7.62m) (Diagonal)
	Throw Distance	0.9m – 11m
	Throw Ratio	1.5–1.8:1
	Lamp	230W UHB, 2000 hours (3000 hours <sup>2</sup> )
	Brightness	3100 ANSI lumens (typical), 2600 (Eco mode)
	Contrast Ratio	400:1 (typ.)
	Aspect Ratio	4:3 (native), 16:9
<b>AUDIO</b>	Speakers	4x3 watt
<b>INPUT SIGNAL</b>	Computer and Video	RGB analogue, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM, SDTV (480i/p, 576i/p), HDTV (720p, 1080i)
	Frequency	F <sub>H</sub> : 15–91kHz; F <sub>V</sub> : 56–120Hz
<b>COMPATIBILITY</b>	PC	Analogue: from VGA up to UXGA (scaled), 1024 x 768 @ 60 Hz preferred
	Mac <sup>®3</sup>	Analogue: up to SXGA (scaled), 1024 x 768 @ 60 Hz preferred
<b>CONNECTOR</b>	RGB (in)	2 x 15-pin mini D-sub
	RGB (out)	1 x 15-pin mini D-sub
	DVI (in)	1 x DVI (HDCP enabled)
	Composite Video (in)	1 x RCA jack
	S-Video (in)	1 x 4-pin mini-DIN
	Component Video (in)	1 x RCA jack
	Audio (in)	1 x 3.5mm stereo mini jack (for PC-RGB), 1x RCA set L/R jack (for video)
	Audio (out)	1 x 3.5mm stereo mini jack
	USB	1 x USB Typ B for mouse control
Control/Network	1 x 9-pin D-sub RS232, 1 x RJ45	
<b>POWER</b>	Voltage	AC 100-120/220-240 VAC, 50/60Hz (universal)
	Consumption	370W (typ.)
<b>CONTROLS</b>	Basic	Standby, menu, input, reset, H/V keystone correction
	OSD	Auto adjust, brightness, contrast, Gamma, colour temperature, colour, tint, sharpness, My Memory, aspect ratio, overscan, H/V position, fine tune, H size, progressive scan, 3D-YCS, Video NR, colour space, component, video format, DVI, information, Eco mode, projection (front, rear, ceiling), volume, IR remote, language, OSD position, OSD background, blank screen, start up, MyScreen, MyScreen lock, message, one touch, auto source detection, auto off, lamp timer, filter timer, service, network adjust (DHCP, IP, Subnet, Gateway, information), pinlock
<b>OPERATING CONDITIONS</b>	Temperature	0°C–35°C
	Humidity	10%–85% (non-condensing)
<b>NOISE LEVEL</b>	Normal	38dB (typ.)
	Eco mode	33dB (typ.)
<b>DIMENSIONS</b>	(W x H x D mm)	336 x 95 x 265 (physical) 444 x 416 x 380 (packaging)
	<b>WEIGHT</b>	Net 4.0kg Gross 9.2kg
<b>REGULATIONS</b>		CE, CB, UL-DEMKO/GS, UL 60950, C-UL, FCC-B, C-TICK, NOM, TÜV-S, WEEE, RoHS
<b>PACKAGE CONTENTS</b>		3LCD Projector, power cords, VGA cable, RCA video cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

### OPTIONAL ACCESSORIES

- > Replacement lamp RLC-003
- > Hard case with wheels PRJ-HCA-002
- > Universal ceiling mount kit WMK-005



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

#### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

#### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

#### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

#### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

#### ViewSonic Belux

#### ViewSonic Denmark

#### ViewSonic Finland

#### ViewSonic Italy

#### ViewSonic MEA

#### ViewSonic Netherlands

#### ViewSonic Norway

#### ViewSonic Spain

#### ViewSonic Sweden

Tel: +32 (0)56 85 26 27

Tel: +45 70 22 11 71

Tel: +358 20 7120 860

Tel: +39 02 73 95 50 22

Tel: +971 (0) 4 88 11 871

Tel: +31 (0)20 491 9254

Tel: +47 (0) 22 88 17 60

Tel: +34 (0) 91 63 05 339

Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> Optional cables required. <sup>2</sup> Running Eco mode exclusively can extend lamp life. <sup>3</sup> May require optional Mac adapter.

Copyright © 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ862-05/07-UK