

# PJD5111

## LIGHT, BRIGHT AND VERSATILE DLP PROJECTOR

WITH BRILLIANTCOLOR™ TECHNOLOGY

## Easy to use, easy to afford

The ViewSonic PJD5111 is a practical projector that offers outstanding value and the best SVGA performance available. This native SVGA resolution projector supports high definition signals and projects 2500 lumens for clear, bright images in most lighting conditions. At only 2.3kg, it is light and compact, making it ideal for the mobile presenter or to move from room to room in the office or on a campus. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5111 is an excellent multifunctional data/video projector. The Eco-mode function reduces the fan noise output for less distraction during important presentations and even extends the lamp life up to 4000 hours\*. The PJD5111 is perfect for users looking for an easy to use, versatile and portable projector at a great price.



### Versatile presentations anywhere

#### > Advanced connectivity

In addition to standard connectors, this projector provides two RGB inputs to easily switch between presenters and an additional RGB output to connect to an external monitor.

#### > BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.

#### > Bright in virtually any setting

Packs 2,500 ANSI lumens in just 2.3kg, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

#### > Eco-mode extends lamp life

Extend the life of your lamp up to 4000 hours\*\* and reduce noise output to whisper quiet 26 db.

#### > Off-To-Go feature

The direct-off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™

# PJD5111

**ViewSonic®**  
See the difference™ 

## LIGHT, BRIGHT AND VERSATILE DLP PROJECTOR

Model No.VS12440



### Optional Accessories

- >Replacement lamp RLC-047
- >Universal ceiling mount kit WMK-018
- >Wireless G presentation gateway WPG-150
- >3 year extended lamp warranty LSWP3

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
M	feet	m	Inches
1.2	3.9	0.7~0.8	28.0~31.7
1.5	4.9	0.9~1.0	35.2~40.0
1.8	5.9	1.1~1.2	42.3~48.0
2	6.6	1.2~1.3	47.4~53.7
3	9.8	1.8~2.2	70.3~79.7
5	16.4	3.3~3.4	117.6~133.3
11.3	37.1	6.4~7.6	250~300



ISO 9001:2000  
FM 40187

ISO 14001:1996  
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic Europe Limited/UK**  
Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom  
Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany  
Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France  
Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA  
Tel: +1 909 869 7976  
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

Rev.1.0

<b>DISPLAY</b>	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	SVGA 800×600 (Native) / SXGA 1280×1024 (compressed)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	35"-155" / 0.89m-3.9m
	Throw Distance	1.5m-6m / 4.9ft-19.7ft / 59.05"-236.2"
	Throw Ratio	1.86:1-2.04:1
	Lamp	189 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000* hours
	Brightness	2500 Lumens
	Contrast Ratio	2800:1 (with DCR)
	Aspect Ratio	4:3 (native) & 16:9
	Color Gamut	85 % NTSC 1931 CIE
<b>AUDIO</b>	Speaker	5W×1
<b>INPUT SIGNAL</b>	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 30-70 KHz, Fv: 50-87 Hz
<b>COMPATIBILITY</b>	PC	VGA to SXGA
	Mac	Up to 1280×1024 (may require Mac Adapter)
<b>CONNECTOR</b>	RGB Input	2 × 15-pin mini D-sub
	Component	2 × 15-in mini -D-Sub (sharer with RGB)
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
<b>POWER</b>	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	242W (Typical) / <5W (Stand-by mode)
<b>LANGUAGE</b>		English, French, German, Italian, Spanish, Russian, Traditional Chinese, Simplified Chinese, Japanese, Korean, Swedish, Dutch, Turkish, Czech, Portuguese, Thai, Polish, Finnish
<b>CONTROLS</b>	Keypad	Power, keystone/up and down keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	<b>Display:</b> Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom <b>Picture:</b> Preset mode: brightest, standard (Video), daylight, ViewMatch (PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness, BrilliantColor™, color temp., save settings <b>Source:</b> Quick auto search <b>System setting (Basic):</b> Language, projector position, auto power off, blank timer, panel key lock, timer controller, splash screen <b>System setting (Advanced):</b> Quick cooling, high altitude mode, DCR, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings <b>Information:</b> Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
<b>OPERATING CONDITION</b>	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~1,800m (6000ft), operational up to 3,048m (10000ft)
<b>NOISE LEVEL</b>	Normal / Eco Mode	30dB / 26dB
<b>DIMENSIONS (W x D x H)</b>	Physical	264 × 225 × 96.4 (mm) / 10.4 × 8.86 × 3.8 (in)
	Packaging	340 × 273 × 190 (mm) / 13.39 × 10.75 × 7.48 (in)
<b>WEIGHT</b>	Net	2.3 kg (5.08lb)
<b>REGULATIONS</b>		CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
<b>PACKAGE CONTENTS</b>		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
<b>WARRANTY</b>		3-year limited warranty on parts, 1-year limited warranty on lamp

\*Requires SRS Audio Sandbox Software to be installed. \*\*Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD5351

For more product information, visit us on the web at [viewsoniceurope.com](http://viewsoniceurope.com)