

PJD7583w

Professional Widescreen High-Definition Projector

Short Distance – Big Presentations

The PJD7583w is a feature-rich WXGA ultra short throw 3D-ready DLP® projector. With its ultra short throw lens, it can project a large 95-inch image from just 3 feet away. The PJD7583w equips with the latest BrilliantColor™ technology to produce vivid colors, while 3000 lumens and 3000:1 dynamic contrast ratio make your images look great in any lighting situation. Multiple display options such as dual RGB ports, RJ45 network display, USB plug-n-play, PC-less presentation and WiFi (with optional adapter) provide ultimate flexibility. With its advance management software, multiple projectors can be displayed and controlled over the network from a single computer. The ViewSonic PJD7583w is the perfect projector for diverse business and education applications.



Short throw lens for large stunning images in small places

The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 95-inch is possible from just 39 inches.

Network display

With its advanced management software, you can project up to 4 PCs at the same time with the ability to broadcast up to 8 projectors

Network control through RJ45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

BrilliantColor™ technology

BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

USB display

Project your presentations through any USB connection without the hassle of running a bulky VGA cable.

Eco-mode extends lamp life

Extend the life of your lamp up to 6,000 hours and reduce noise output.

PC-Less slideshow presentation

Project your pictures or images directly from a USB flash drive without a PC.

Wireless capability

Allow the projector to be WiFi enabled with an optional USB wireless adapter (WPD-100).

Supports Crestron RoomView® Express

Manage up to 250 network projectors in real time monitoring and control. Manage assets, schedule events and program email alerts with this amazing software.

ViewSonic®
See the difference™ 

PJD7583w

Smartly Connects You to Widescreen Viewing Experience



Optional Accessories

- 3D Goggle PGD-150
 Replacement lamp RLC-057
 Ceiling mount WMK-025
 3D Convector VP3DI
 Wireless Dongle WPD-100

Projection Distance		16:10 Screen Size		Vertical offset	
Wide					
M	inch	M	inch	cm	inch
0.32	12	0.8	30	2	0.8
0.42	17	1	40	3	1.1
0.53	21	1.3	50	3	1.3
0.63	25	1.5	60	4	1.6
0.74	29	1.8	70	5	1.9
0.84	33	2	80	5	2.1
0.95	37	2.3	90	6	2.4
1.05	41	2.5	100	7	2.6
1.26	50	3	120	8	3.2
1.58	62	3.8	150	10	4
2.11	83	5.1	200	13	5.3
2.63	104	6.4	250	17	6.6
3.16	124	7.6	300	20	7.9



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Model Name		PJD7583w
DISPLAY	Type	0.65" Digital Micromirror Device (DLP™)
	Resolution	WXGA 1280 × 800
	Lens	Manual focus / Fixed Zoom
	Size	30"-300"
	Throw Distance	0.32m - 3.16m
	Throw Ratio	0.5
	Lamp	210w
	Lamp Life (Normal/EcoMode)	4000 / 6000 (hours)
	Brightness	3000 lumens
	Contrast Ratio	3000:1
	Color Depth	24 bits, 1.67 M Colors (8+8+8)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	99 % NTSC 1931 CIE
	Keystone	Vertical digital keystone correction: ± 40 degrees
AUDIO	Speaker	10w x 1
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz
		PAL (B, D, G, H, I, M, N, 60)
		SECAM (B, D, G, K, K1, L)
		480i and 576i / 480p and 576p / 720p, 1080i
	Video	NTSC, PAL
	HD	HD (720p, 1080i)
	Frequency	Fh: 31-100 KHz, Fv: 48-120 Hz
COMPATABILITY	PC	XGA to UXGA
	Mac	Up to 1400×1050 (may require Mac Adapter)
CONNECTOR	RGB Input/ Output	2×15-pin mini D-sub / 1×15-pin mini D-sub
	Composite Input	1×RCA jack
	S-Video Input	1 x 4-pin mini DIN
	Audio Input	1×3.5mm mini jack(Microphone) / RCA x1
	Audio Output	1×3.5mm mini jack
	USB	Mini type A (x1) (For PCLess Presentations) Mini type B (x1) (For Mouse Control)
	Control	1×RS-232 (9 Pin D-Sub)
	DC Output	12V trigger
	Lan	RJ-45
	POWER	Voltage
Power Consumption		329W (Typical) / <1W (RGB out disable)
NOISE LEVEL	Normal / Eco Mode	34dB / 29dB
LANGUAGE	English/ France / Germany/ Italian/ Spanish/ Russian/ T. Chinese / S. Chinese / Japanese/ Korean/ Swedish/ Dutch/ Turkish/Czech/ Portuguese/ Thai/ Polish/ Finnish	
	OPERATING Temperature	0°C-40°C
	CONDITION Humidity	10%-90%(non-condensing)
	DIMENSIONS Physical	290 mm (W) x 254mm (D) x 126 mm (H)
WEIGHT	Net	3.5kg
REGULATIONS	CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, TUV-GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS	
	WARRANTY	3 years
	LAMP	1 year
WARRANTY		

For more product information, visit us at:

www.viewsoniceurope.com

ViewSonic®
See the difference™