

VA1703wb

**17" WIDESCREEN LCD
MONITOR VA SERIES**
WITH 8MS VIDEO RESPONSE TIME

Widescreen enjoyment for all

ViewSonic's 17" VA1703wb LCD brings panoramic widescreen to everyone. The 16:10 wide aspect ratio and high 1440 x 900 resolution provide AMPLE SPACE FOR MULTIPLE DOCUMENT WINDOWS, side-by-side full-page layouts, and immersive gaming that virtually surrounds the user. With ClearMotiv® video response, you get to enjoy extreme clarity, amazing colour and stunning brightness. The VA1703wb delivers on ViewSonic's tradition of BRILLIANT IMAGE QUALITY AND RELIABLE PERFORMANCE all at an attractive price. It's the easy choice for gamers, home/small office users and corporate professionals.

It's not just another widescreen LCD. It's a ViewSonic.



LIFESTYLE ENJOYMENT WORKPLACE PRODUCTIVITY

- > **Fast 8ms video response delivers superior picture clarity**
- > **Full 17" viewable widescreen**
Displays a full, flat 17" viewable widescreen area with crisp detail and fully saturated colour.
- > **1440 x 900 native resolution**
Incredible image detail for sharp text and graphics.
- > **High brightness and contrast**
250cd/m² brightness (typ.) and 500:1 contrast ratio (typ.) for rich, detailed images.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**
Prevents changes to monitor settings and maintains an optimized image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments can be made precisely via an easy-to-use on-screen menu.
- > **Integrated power supply**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac® compatible**
- > **MPR II and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

VA1703wb

17" WIDESCREEN LCD MONITOR VA SERIES WITH 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	17" Wide TN colour TFT active matrix WXGA+ LCD
	Display Area	36.7cm horizontal x 23.0cm vertical, 43.2cm diagonal
	Pixel Pitch	0.255mm
	Optimum Resolution	1440 x 900@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	500:1 (typ.)
	Viewing Angle	150° horizontal, 130° vertical (at 10:1) 160° horizontal, 150° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	262k colours supported (6-bit)
	Light Source	Long life, 30000 (min.)
	Brightness	250cd/m ²
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Frequency	F _H : 24-82kHz, F _V : 50-75Hz
	Synchronisation	H/V separate (TTL)
COMPATIBILITY	PC	VGA up to 1440 x 900 non-interlaced
	Mac ¹	Power Mac™ G3/G4/G5 up to 1440 x 900 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100-240V, 50/60Hz (auto switch), internal power supply
	Consumption	25 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C-40°C
	Humidity	10%-80% (non-condensation)
DIMENSIONS	(W x H x D mm)	407 x 375 x 210 (with stand) 407 x 293 x 63 (without stand) 456 x 420 x 156 (packaging)
WEIGHT	Net	3.2kg (with stand) 2.9kg (without stand)
	Gross	4.0kg
REGULATIONS		NEMKO/GS ² , NEMKO/ERGO ³ , ISO 13406-2 (pixel failure class II), CE, CB, GOST-R+Hygienic (3 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, MIC, BSMI, PSB, MPR II, VCCI, CCC, WEEE, RoHS
POWER MANAGEMENT		Meets MPR II and ENERGY STAR standards
SECURITY		Kensington security port
WALL MOUNT		VESA FDMI 75mm x 75mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark
ViewSonic Finland
ViewSonic MEA
ViewSonic Netherlands
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Equivalent to TÜV/GS. ³ Equivalent to TÜV/ERGO.