

# VA1716w

**17" WIDESCREEN LCD  
MONITOR VA SERIES**  
WITH 8MS VIDEO RESPONSE TIME

## Budget-friendly widescreen

ViewSonic's 17" VA1716w LCD brings you widescreen performance at a great price point. The 16:10 aspect ratio and high 1440 x 900 resolution allow you to view two documents side-by-side or to WORK IN MULTIPLE APPLICATIONS SIMULTANEOUSLY. PC gamers will appreciate the immersive gaming action delivered by fast ClearMotiv® video response. You'll be amazed by the EXTREME CLARITY AND BRILLIANT COLOURS of the VA1716w. This widescreen LCD continues ViewSonic's tradition of brilliant image quality and reliable performance all at an appealing price point. It's the easy choice for gamers, home/small office users and corporate professionals.

**It's not just another widescreen LCD. It's a ViewSonic.**



### MORE PRODUCTIVITY. MORE FUN.

- > Fast 8ms video response delivers superior picture clarity
- > Full 17" viewable widescreen  
Displays a full, flat 17" viewable widescreen area with crisp detail and fully saturated colour.
- > 1440 x 900 native resolution  
Incredible image detail for sharp text and graphics.
- > 2000:1 dynamic contrast ratio
- > Stylish slim-bezel design  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OSD/power lock secures your settings  
Prevents changes to monitor settings and maintains an optimized image.
- > OnView® controls for superior screen adjustability  
Screen adjustments can be made precisely via an easy-to-use on-screen menu.
- > Integrated power supply
- > Windows Vista approved
- > ViewSonic Wizard included  
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > PC and Mac® compatible
- > MPR II and ENERGY STAR® qualified



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# VA1716w

## 17" WIDESCREEN LCD MONITOR VA SERIES WITH 8MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	17" Wide TN colour TFT active matrix WXGA+ LCD
	Display Area	36.7cm horizontal x 23.0cm vertical, 43.2cm diagonal
	Pixel Pitch	0.255mm
	Optimum Resolution	1440 x 900@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	500:1 (typ.), 2000:1 (DCR)
	Viewing Angle	140° horizontal, 130° vertical (at 10:1) 160° horizontal, 160° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	262k colours (6-bit)
	Light Source	Long life, 30000 (typ.)
	Brightness	250cd/m <sup>2</sup>
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Frequency	F <sub>H</sub> : 30–82kHz, F <sub>V</sub> : 50–75Hz
	Synchronisation	H/V separate (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1440 x 900 non-interlaced
	Mac <sup>1</sup>	Power Mac™ G3/G4/G5 up to 1440 x 900
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	20W (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	0°C–40°C
	Humidity	5%–85% (non-condensation)
<b>DIMENSIONS</b>	(W x H x D mm)	398 x 360 x 195 (with stand) 398 x 280 x 62 (without stand) 453 x 415 x 148 (packaging)
<b>WEIGHT</b>	Net	3.2kg (with stand) 2.9kg (without stand)
	Gross	4.2kg
<b>REGULATIONS</b>		CE, CB, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), UL, cUL, GOST-R, FCC-B, NOM, SASO, ENERGY STAR, C-Tick, BSMI, PSB, MPR II, VCCI, CCC, WEEE, RoHS
<b>POWER MANAGEMENT</b>		MPR II and ENERGY STAR standards
<b>SECURITY</b>		Kensington security port
<b>WALL MOUNT</b>		VESA FDMI 75mm x 75mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbanniers  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

### ViewSonic Denmark

### ViewSonic Finland

### ViewSonic MEA

### ViewSonic Netherlands

### ViewSonic Norway

### ViewSonic Spain

### ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.