

VA2226w

**22" WIDESCREEN LCD
MONITOR VA SERIES
WITH DIGITAL HDCP INPUT**

Get the big picture

The ViewSonic VA2226w provides large 22" widescreen desktop viewing, including future-proofed OptiSync technology with HDCP at an affordable price. This large 16:10 aspect ratio LCD lets you see more and work more efficiently. Have two applications or documents open side-by-side. Experience games and movies in a fantastic new big cinema format. Thanks to the new advanced Dynamic Contrast Ratio, your images, graphics and videos will appear crystal-clear with colour like you've never seen before. The fast 5ms video response time guarantees blur-free videos and graphics without ghosting. OptiSync technology adds versatile and future-proofed connectivity, offering digital (with HDCP) and analogue inputs. The VA2226w is the ideal choice for those looking for a wider view while staying within their business budget.

It's not just another digital widescreen LCD. It's a ViewSonic.



WIDESCREEN – HIGH ENJOYMENT, ENHANCED PRODUCTIVITY

- > **2000:1 Dynamic Contrast Ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **Super fast 5ms video response delivers superior picture clarity**
- > **Full 22" viewable widescreen**
Displays a full, flat 22" viewable widescreen area with crisp detail and fully saturated colour.
- > **1680 x 1050 native resolution**
Incredible image detail for sharp text and graphics.
- > **OptiSync® multiple analogue/digital inputs**
Multi-mode input technology supports both digital (DVI-HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **Ultra-wide viewing angles extend your view**
- > **OnView® controls for superior screen adjustability**
- > **Windows Vista approved**
- > **ViewSonic Wizard included**
User-friendly Wizard software automates the setup process to deliver optimized screen performance.
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

VA2226w

22" WIDESCREEN LCD MONITOR VA SERIES WITH DIGITAL HDCP INPUT



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	22" Wide TN colour TFT active matrix WSXGA+ LCD
	Display Area	47.4cm horizontal x 29.6cm vertical, 55.9cm diagonal
	Pixel Pitch	0.282mm
	Optimum Resolution	1680 x 1050@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	1000:1 (typ.), 2000:1 (DCR, typ.)
	Viewing Angle	170° horizontal, 160° vertical (at 10:1) 175° horizontal, 170° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.7M colours supported (6-bit+2-bit HI FRC)
	Light Source	Long life, 40000 hours (min.)
	Brightness	300cd/m ²
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Digital	DVI-D (HDCP enabled, TMDS, 100 ohm, DDC/CI)
	Frequency	F _H : 24-82kHz, F _V : 50-75Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1680 x 1050 non-interlaced
	Mac ¹	Power Mac™ up to 1680 x 1050 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable) (HDCP enabled)
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100-240V, 50/60Hz (auto switch), internal power supply
	Consumption	38 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD ²	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), auto white balance, OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C-40°C
	Humidity	20%-90% (non-condensation)
DIMENSIONS	(W x H x D mm)	510 x 432 x 225 (with stand) 510 x 351 x 61 (without stand) 560 x 474 x 124 (packaging)
WEIGHT	Net	5.1kg (with stand)
	Gross	6.6kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS
POWER MANAGEMENT		TCO'03 and ENERGY STAR standards
SECURITY		Kensington security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)20 7120 860
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Some features may not be available on all inputs.