

VA2232w

56cm/22" VALUE SERIES WIDESCREEN LCD DISPLAY

Super Contrast Ratio Widescreen



- > **Fast 5ms video response delivers superior picture clarity**
- > **Full 56cm/22" viewable widescreen**
Displays a full, flat 56cm/22" viewable area with crisp detail and fully saturated color.
- > **1680 X 1050 native resolution**
Incredible image detail for sharp text and graphics.
- > **100,000:1 dynamic contrast ratio typical**
Provides for darker black levels and better overall front-of-screen performance.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**
Prevents unauthorised changes to monitor settings and maintains your optimised image.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows 7 approved**
- > **Eco modes, to reduce operating power consumption by up to 40%**
- > **PC and Mac® compatible**



Model Name:	VA2232w	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (Typ.) Dynamic Contrast Ratio Viewing Angle (CR \geq 10 / CR \geq 5) Response Time (ms) Pixel Pitch (H×V) Panel Surface Light Source (Hours) Colour Support (Millions of colours)	56cm/22" Wide Colour a-Si TFT Active Matrix LCD 16:10 aspect ratio 1680 × 1050 native resolution 300 Typical 1,000:1 100,000:1 170° (H), 160° (V) 5ms Typical 0.282 × 0.282 (mm) Anti-Glare, Hard coating(3H) 50,000 hrs minimum 16.7 M
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) Separate Fh = 24 – 82kHz; Fv = 50 – 75 Hz, (VGA)
COMPATIBILITY	PC Mac	VGA up to 1680 × 1050 Non Interlaced Mac OS up to 1680 × 1050
CONNECTOR	Analogue Digital Power	1 × 15 pin mini D-sub 1 × DVI-D Built-in power Adapter, 3-Pin plug
POWER	Voltage Consumption (W) Save mode (W)	AC 100-240V (Universal); 50/60Hz(Switch) 38 Typical / 45 Maximum \leq 0.5W
ERGONOMICS CONTROLS	Tilt Basic OnView / OSD	20--5 degrees [1], [2], Power, Down[▼], Up[▲] Auto Image Adjust, Contrast/Brightness, Color Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B] Information, Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Eco mode, Setup Menu, Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, Auto Power Off, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 5 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	510 × 416.2 × 195.4 (mm) / 20.1 × 16.4 × 7.7 (in)
WEIGHT REGULATIONS	Net (w/ stand)	4.7 kg / 10.36 lb CB, WEEE, RoHS, REACH SVHC List, CE, Nemko ERGO, GOST-R+Hygienic, UkrSEPRO BSMI, PSB, C-TICK, KC, SASO
WALL MOUNT (mm)	VESA® Mount Compliant	100mm × 100mm