

ViewSonic® VA912 LCD Monitor

19" VALUE SERIES LCD DISPLAY



Value-packed and stylish.

The 19" ViewSonic VA912 LCD display is the **ALL-IN-ONE PRICE PERFORMANCE SOLUTION FOR MIXED DATA, AUDIO, GRAPHICS AND VIDEO CONTENT**. This LCD is packed with features not normally found in a value display. **CLEARMOTIV™ BROADCAST-QUALITY VIDEO**, 8ms response, an ultra-high 600:1 (typ.) contrast ratio and 160° viewing angles all **ENSURE INTENSE VISUAL PERFORMANCE**. Enjoy a true multimedia experience with less clutter and components on the desktop. Look to the VA912 LCD display for affordability without compromise for small/home office, corporate, government or education use.

Affordability without compromise.

... High brightness and contrast

250cd/m² brightness (typ.) and 600:1 contrast ratio (typ.) for rich, detailed images

... 1280 x 1024 resolution

... Full 19" viewable

... ClearMotiv™ technology

Fast 8ms video response delivers broadcast-quality full motion video.

... Multimedia enhanced

Save desk and workspace and enjoy rich stereo sound with built-in stereo speakers.

... Stylish slim-bezel design

The full 19" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.

... OnView® controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

... VESA® 100mm wall mount interface and Kensington® security port

... PC and Mac® compatible

... TCO'99 and ENERGY qualified

... **OPTISYNC** digital/analogue inputs expand your connectivity options

Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.

Value

ViewSonic® 
the choice of professionals

ViewSonic® VA912 LCD Monitor

19" VALUE SERIES LCD DISPLAY



1. One-touch buttons control all major functions
2. Space-saving slim-line design is only 6.8cm thick
3. Compact, multimedia, attractive styling



Available colours:
Black/Silver dual tone

19" LCD MONITOR WITH CLEARMOTIV™ AND MULTIMEDIA

LCD PANEL	Type	19" colour TN TFT active matrix SXGA LCD
	Display Area	376mm horizontal x 301mm vertical, 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Contrast Ratio	600:1 (typ.)
	Viewing Angles	140° horizontal, 130° vertical (at 10:1) 150° horizontal, 160° vertical (at 5:1)
	Response Time	8ms (typ.)
	Colour Support	16.2M colours (6-bit + 2-bit FRC)
	Light Source	Long life, 40,000 hrs. (typ.)
	Brightness	250cd/m ² (typ.)
	Panel Surface	Anti-glare
INPUT SIGNAL	Analogue	RGB analogue (75 ohms, 0.7 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Sync	H/V separate (TTL)
	Frequency	Fh: 30~82kHz, Fv: 50~85Hz
COMPATIBILITY	PC	VGA up to 1280 x 1024 (up to 75Hz)
	Mac¹	Power Mac™ G3/G4/G5 up to 1280 x 1024 @ 75 Hz
CONNECTOR	Analogue	15-pin mini D-sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	Stereo mini audio line in
POWER	Voltage	AC 100–240V (universal), 50–60Hz (auto switch), internal power supply
	Consumption	< 60W (typ.); ≤ 3 watt in power save mode
AUDIO	Speakers	2 x 1.5 watt
	Amplifier	1.5 watt @ THD < 8%
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Physical	Power on/off, menu, up, down, select
	OSD	Auto image adjust, brightness, contrast, input select (analogue, digital), colour adjust (sRGB, 9300K, 6800K, 6500K, user RGB), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	Temperature	0°C to 40°C
	Humidity	10% to 90% (no condensing)
DIMENSIONS	(W X H X D mm)	424 x 442 x 186 (with stand)
WEIGHT	Net	5.5kg
REGULATIONS		CE, CB, TUV/GS, TUV/ERGO, ISO13406-2 (pixel failure class II), TCO'99, UL, cUL, FCC-B, ENERGY, NOM, TUV-S, MPR II, GOST-R + 20 original copies hygienic, PCBC, VCCI, BSMI, CCC, PSB, C-TICK
POWER MANAGEMENT		Meets TCO'99 and ENERGY standards
WARRANTY		Please see: www.viewsoniceurope.com/uk/Support/warranty.htm



ViewSonic Corporation's OMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

ViewSonic 

the choice of professionals

¹May require optional Mac adapter

Copyright © 2006 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. VS VA912-03/06-UK