

# VA926

## 19" LCD MONITOR VA SERIES

WITH 5MS RESPONSE TIME AND DVI

## Budget-savvy desktop space saver

ViewSonic's 19" VA926 LCD is a brilliant choice for upgrading your home or small office. This ultra-slim, Vista-certified LCD DELIVERS AN IMPRESSIVE ARRAY OF FEATURES that will enhance your productivity while helping you stay within your budget. With OptiSync digital and analogue inputs, a 2000:1 DYNAMIC CONTRAST RATIO (typ.) and fast ClearMotiv® 5ms video response, you'll enjoy crystal-clear graphics, video and text. The latest OSD/power lock and AutoTune® functions MAXIMISE AND MAINTAIN YOUR DISPLAY SETTINGS. The VA926 displays excellent taste while enhancing your home or small office desktop.

**It's not just another LCD monitor. It's a ViewSonic.**



### ATTRACTIVE STYLING. ATTRACTIVE PRICE.

- > **2000:1 Dynamic Contrast Ratio**  
Provides for darker black levels and better overall front-of-screen performance.
- > **Super fast 5ms video response delivers superior picture clarity**
- > **Full 19" viewable screen**  
Displays a full, flat 19" viewable area with crisp detail and fully saturated colour.
- > **1280 x 1024 native resolution**  
Incredible image detail for sharp text and graphics.
- > **OptiSync® multiple analogue/digital inputs**  
Multi-mode input technology supports both digital (DVI-HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintains an optimised image.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Windows Vista approved**
- > **ViewSonic Wizard included**  
User-friendly Wizard software automates the setup process to deliver optimised screen performance.
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# VA926

## 19" LCD MONITOR VA SERIES WITH 5MS RESPONSE TIME AND DVI



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	19" TN colour TFT active matrix SXGA LCD	
	Display Area	37.6cm horizontal x 30.1cm vertical, 48.3 cm diagonal	
	Pixel Pitch	0.294mm	
	Optimum Resolution	1280 x 1024@60Hz	
	Pixel Clock	140MHz	
	Contrast Ratio	1000:1 (typ.), 2000:1 DCR (typ.)	
	Viewing Angle	170° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)	
	Response Time	5ms (off-on-off) (typ.)	
	Colour Support	16.7M colours supported (6-bit + 2-bit FRC)	
	Light Source	Long life, 40000 (typ.)	
	Brightness	300cd/m <sup>2</sup>	
Panel Surface	Anti-glare		
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)	
	Digital	DVI-D (TMDS, 100 ohm)	
	Frequency	F <sub>H</sub> : 30–82kHz, F <sub>V</sub> : 50–75Hz	
	Synchronisation	H/V separate (TTL)	
<b>COMPATIBILITY</b>	PC	VGA up to 1280 x 1024 non-interlaced	
	Mac <sup>1</sup>	Power Mac™ up to 1280 x 1024 non-interlaced	
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)	
	Digital	24-pin DVI-D (detachable cable)	
	Power	3-pin AC plug (CEE22)	
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply	
	Consumption	32 watt (typ.), <1 watt in power save mode	
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°	
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2]	
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), auto white balance, OSD/power lock, memory recall	
<b>OPERATING CONDITIONS</b>	Temperature	0°C–40°C	
	Humidity	10%–90% (non-condensation)	
<b>DIMENSIONS</b>	(W x H x D mm)	412 x 435 x 194 (with stand) 412 x 355 x 64 (without stand) 470 x 510 x 140 (packaging)	
	<b>WEIGHT</b>	Net	3.8kg (with stand), 3.3kg (without stand)
		Gross	5.0kg
<b>REGULATIONS</b>		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS	
<b>POWER MANAGEMENT</b>		TCO'03 and ENERGY STAR standards	
<b>SECURITY</b>		Kensington security port	
<b>WALL MOUNT</b>		VESA FDMI 100mm x 100mm	
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)	
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>	

### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

### ViewSonic Denmark

### ViewSonic Finland

### ViewSonic MEA

### ViewSonic Netherlands

### ViewSonic Norway

### ViewSonic Spain

### ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.