VG2030wm 20" WIDESCREEN GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Panoramic widescreen display

The ViewSonic 20" VG2030wm features 16:10 WIDESCREEN format with 1680 x 1050 optimum resolution and ERGONOMIC HEIGHT ADJUSTMENT. View two documents side-by-side or work in two applications simultaneously to improve productivity. High 300cd/m² brightness and ultra-high 800:1 contrast ratio produce bright, crisp, detailed images. Graphics professionals love the FAST 5MS RESPONSE TIME that delivers blur-free, full motion video. Digital and analogue inputs ensure maximum connectivity options while height adjustment, tilt and 360° swivel settings guarantee the best possible viewing position ensuring you'll work comfortably for hours. Further, built-in stereo speakers provide multimedia performance without desk clutter. The VG2030wm is the stand-out price/performance choice, offering lifestyle enjoyment and workplace productivity in a single stunning package.

It's not just a digital widescreen LCD monitor. It's a ViewSonic.



EXPAND YOUR DESKTOP EXPERIENCE

- Stylish slim-bezel design The full 20" viewable widescreen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > Ergonomic base adds ease and comfort

 Ultimate ergonomic flexibility comes built-in with the convenient 80mm height adjustment and 360° swivel.
- > High 300cd/m² brightness (typ.) and 800:1 contrast ratio (typ.)
- > ClearMotiv™ 5ms video response time
 Fast 5ms video response delivers broadcast-quality video.
- > Dynamic Structure™ technology
 Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > OptiSync® digital/analogue inputs expand your connectivity
 Multi-mode input technology supports both digital (DVI) and
 analogue (VGA) signals for ultimate compatibility and configuration
 flexibility.
- Multimedia enhanced
 Save workspace and enjoy rich stereo sound with two built-in stereo speakers.
- > VESA 100mm wall mount interface and Kensington® security port
- > TCO'03 and Energy Star® qualified
- > PC and Mac® compatible





VG2030wm

20" WIDESCREEN GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST















LCD	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock	20" Wide TN colour TFT active matrix WSXGA+ LCD 43.3cm horizontal x 27.1cm vertical; 51.1cm diagonal 0.258mm 1680 x 1050@60Hz 165MHz
	Contrast Ratio Viewing Angles	800:1 (typ.) 160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time Colour Support Light Source Brightness Panel Surface	5ms (off-on-off) (typ.) 16.7M colours (6-bit+Hi FRC) Long life, 60000 hrs. (typ.) 300cd/m² Anti-glare
VIDEO INPUT	Analogue Digital Frequency Synchronisation	RGB analogue (0.7 Vp-p, 75 ohm) DVI-D (TMDS, 100 ohm) Fh: 24–82kHz, Fv: 50–85Hz H/V separate (TTL), sync on green
COMPATIBILITY	PC Mac ¹	VGA up to 1680 x 1050 non-interlaced Power Mac™ G3/G4/G5 up to 1680 x 1050 non-interlaced
CONNECTOR	Analogue Digital Audio Power	15-pin mini D-Sub (detachable cable) 24-pin DVI-D (detachable cable) 3.5mm stereo audio line-in 3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 2 watt integrated stereo speakers
POWER	Voltage Consumption	AC 100– 240V, 50/60Hz (auto switch), internal power supply 43 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt Swivel Height Adjustment	Down 5°, Up 20° 360° swivel base 0 ~ 80mm
CONTROLS	Basic OSD ²	Power, menu [1], up, down, select [2], mute Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), audio adjust (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature Humidity	3°C − 35°C 20% − 80% (non-condensation)
DIMENSIONS	W x H x D mm	493 x 477-557 x 230 (with stand) 493 x 388 x 70 (without stand) 565 x 545 x 273 (packaging)
WEIGHT	Net Gross	7.0kg (with stand) 9.2kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CB, CE, GOST-R, UL, cUL, FCC-B, ICES-003, NOM, SASO, Energy Star, C-Tick, MIC, BSMI, PSB, MPR II, CCC, WEEE, ROHS
POWER MANAGEMENT		Meets TCO'03 and Energy Star standards
SECURITY		Kensington security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
14/4 DD 44 100 /		

ViewSonic Eur	ope Limited/UK
---------------	----------------

ViewSonic House Fleming Way, Crawley West Sussex, RH10 9GA United Kingdom

Tel: +44 (0) 12 93 64 39 00 Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A 47877 Willich Germany

WARRANTY

Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France Parc des Barbanniers

allée des Bas Tilliers 92230 Gennevilliers France

Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road Walnut California 91789-0708

USA Tel: +1 909 869 7976 Fax: +1 909 869 7958 ViewSonic Belux ViewSonic Denmark ViewSonic Finland ViewSonic Italy ViewSonic MFA ViewSonic Netherlands ViewSonic Norway ViewSonic Spain ViewSonic Sweden

Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 Tel: +358 (0)9 5406 4070 Tel: +39 02 73 95 50 22 Tel: +971 (0) 4 88 11 871 Tel: +31 (0)20 491 9254

Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 Tel: +46 (0) 8 50 71 30 00

Not require optional was adapted. Some features may not available of all hipots. Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG2030wm 11/06-UK

¹May require optional Mac adapter. ² Some features may not available on all inputs.