

## Big screen, big performance

For big performance and even bigger productivity you need a big screen. The ViewSonic VG2230wm features large widescreen multimedia performance for a unique desktop experience. The 22" WIDESCREEN display allows you to view two documents side-by-side or work in two applications simultaneously and the 360° SWIVEL base allows you to share your view with co-workers. The 280cd/m<sup>2</sup> brightness and high 700:1 contrast ratio produce bright, crisp, detailed images whilst analogue and digital inputs ensure versatile connectivity options. Graphics professionals love the FAST 5MS VIDEO RESPONSE TIME that delivers blur-free, full motion video and crystal clear images. And with ERGONOMIC HEIGHT ADJUSTMENT and tilt, you'll work comfortably for hours. The VG2230wm widescreen multimedia LCD delivers a complete visual experience to your desktop.

# VG2230wm

**22" WIDESCREEN  
GRAPHIC SERIES LCD**  
WITH SWIVEL AND HEIGHT ADJUSTMENT

**It's not just a large digital widescreen LCD. It's a ViewSonic.**



### FLEXIBLE, VERSATILE DISPLAY

- > **Stylish slim-bezel design**  
The full 22" viewable widescreen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **Ergonomic base adds ease and comfort**  
Ultimate ergonomic flexibility comes built-in with the convenient 135mm height adjustment, tilt and 360° swivel base.
- > **High 280cd/m<sup>2</sup> brightness (typ.) and 700:1 contrast ratio (typ.)**
- > **OptiSync® digital/analogue inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **ClearMotiv® 5ms video response time**  
Fast 5ms video response delivers broadcast-quality, full-motion video.
- > **Dynamic Structure™ technology**  
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **Multimedia enhanced**  
Save workspace and enjoy rich stereo sound with two built-in speakers.
- > **VESA 100mm wall mount interface and Kensington® security port**
- > **TCO'03 and ENERGY STAR® qualified**
- > **PC and Mac® compatible**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES



**ViewSonic®**  
See the difference™ 

# VG2230wm

## 22" WIDESCREEN GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUSTMENT



<b>LCD</b>	Type	22" Wide TN colour TFT active matrix WSXGA+ LCD
	Display Area	47.6cm horizontal x 29.8cm vertical, 55.9cm diagonal
	Pixel Pitch	0.282mm
	Optimum Resolution	1680 x 1050@60Hz
	Pixel Clock	165MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angles	170° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.7M colours supported (6-bit + 2-bit FRC)
	Light Source	Long life, 60000hrs. (typ.)
	Brightness	280cd/m <sup>2</sup>
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	F <sub>H</sub> : 24-82kHz, F <sub>V</sub> : 50-85Hz
	Synchronisation	H/V separate (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1680 x 1050 non-interlaced
	Mac <sup>1</sup>	Power Mac™ G3/G4/G5 up to 1680 x 1050 non-interlaced
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 2 watt integrated stereo speakers
<b>POWER</b>	Voltage	AC 100- 240V, 50/60Hz (auto switch), internal power supply
	Consumption	43 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
	Swivel	360° swivel base
	Height Adjustment	0~ 135mm
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2], mute, volume up/down
	OSD <sup>2</sup>	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K), information (resolution, H/V frequency, pixel clock, model number, serial number), audio adjust (volume, mute), manual image adjust (H/V position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
<b>DIMENSIONS</b>	W x H x D mm	519 x 436-571 x 250 (with stand) 519 x 392 x 60 (without stand) 570 x 530 x 300 (packaging)
<b>WEIGHT</b>	Net	6.6kg (with stand)
	Gross	8.6kg
<b>REGULATIONS</b>		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CB, CE, GOST-R, UL, cUL, FCC-B, ICES-003, NOM, SASO, ENERGY STAR, C-Tick, MIC, BSMI, PSB, MPR II, Argentina TÜV-S, CCC, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'03 and ENERGY STAR standards
<b>SECURITY</b>		Kensington security port
<b>WALL MOUNT</b>		VESA FDMI 100mm x 100mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>



ViewSonic Corporation's GMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

### ViewSonic Denmark

### ViewSonic Finland

### ViewSonic MEA

### ViewSonic Netherlands

### ViewSonic Norway

### ViewSonic Spain

### ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter. <sup>2</sup> Some features may not be available on all inputs.

Copyright © 2007, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG2230wm 10/07-UK