

## The ideal display for a range of lifestyles

ViewSonic's 19" VX1962wm widescreen LCD offers the perfect balance of performance and style. With its elegant lines, the VX1962wm fits beautifully into your home or office décor and its high-performance features BLEND EFFORTLESSLY INTO YOUR TECHNOLOGY LIFESTYLE. Images leap from the screen with Super-HD 1680 x 1050 resolution, video response as fast as 2ms and 6000:1 DYNAMIC CONTRAST RATIO (typ.). Scrolling text, Internet pages and spreadsheet applications are displayed in crisp, blur-free detail with precise colour. Integrated speakers driven with the included SRS WOW HD software powerfully complete your games, movies and other multimedia applications. Demanding designers, professionals and gamers alike will love the sophisticated performance of the 19" VX1962wm.

**It's not just another digital widescreen LCD. It's a ViewSonic.**

# VX1962wm

**19" HD WIDESCREEN LCD  
WITH 6000:1 DYNAMIC CONTRAST**



### SOPHISTICATION AND PERFORMANCE

- > **Full 19" viewable widescreen with 1680 x 1050 resolution**  
High-resolution panel with 36% more detail than a regular 19" widescreen monitor.
- > **Fast ClearMotiv® video response**  
Video response as fast as 2ms enables digital HD broadcast-quality video.
- > **6000:1 Dynamic Contrast Ratio (typ.)**  
Provides darker black levels with increased details and better overall front-of-screen performance.
- > **Stylish slim-bezel design**  
The thin bezel lets you see more without taking up valuable desktop real estate.
- > **OptiSync® digital/analogue inputs expand your connectivity**  
Multi-mode input technology supports both digital (DVI/HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **SRS WOW HD sound and high quality stereo speakers**
- > **Windows® Vista® Premium certified**
- > **PC and Mac® compatible**
- > **ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®** See the difference™ 

# VX1962wm

**19" HD WIDESCREEN LCD WITH 6000:1 DYNAMIC CONTRAST RATIO**



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock Contrast Ratio Viewing Angle  Response Time Colour Support Light Source Brightness Panel Surface	19" Wide TN colour TFT active matrix WSXGA+ LCD 41.0cm horizontal x 25.7cm vertical, 48.3cm diagonal 0.243mm 1680 x 1050 @60Hz 165MHz 1000:1 (typ.), 6000:1 DCR (typ.) 170° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)  Up to 2ms (grey-to-grey), 5ms (off-on-off) (typ.) 16.7M colours supported (6-bit+2-bit FRC) Long life, 40000 hrs. (min.) 300cd/m <sup>2</sup> (typ.) Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue Digital Frequency Synchronisation	RGB analogue (0.7/1.0 Vp-p, 75 ohm, DDC/CI) DVI-D (HDCP enabled, TMDS, 100 ohm, DDC/CI) F <sub>H</sub> : 24–82kHz, F <sub>V</sub> : 50–75Hz H/V separate (TTL), composite, sync on green
<b>COMPATIBILITY</b>	PC Mac <sup>1</sup>	VGA up to 1680 x 1050 non-interlaced Power Mac™ up to 1680 x 1050 non-interlaced
<b>CONNECTOR</b>	Analogue Digital Audio Power	15-pin mini D-Sub (detachable cable) 24-pin DVI-D (detachable cable) (HDCP enabled) 3.5mm stereo audio line-in 3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 3 watt integrated invisible stereo speakers w. SRS WOW HD <sup>2</sup>
<b>POWER</b>	Voltage Consumption	AC 100–240 V, 50–60 Hz (auto switch), internal power supply 44 watt (typ.), <=1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic OSD <sup>3</sup>	Power, menu [1], select [2], up, down Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), Audio adjust (volume, mute), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5000K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness, DCR [on/off], aspect ratio [1:1, 4:3, 16:9, fill aspect ratio, fill full screen], response time [standard, advanced, ultra-fast]), setup menu (language [11 options], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING-CONDITIONS</b>	Temperature Humidity	0°C–35°C 10%–90% (non-condensation)
<b>DIMENSIONS</b>	W x H x D mm	447 x 399 x 175 (with stand), 447 x 317 x 52 (without stand) 510 x 465 x 135 (packaging)
<b>WEIGHT</b>		3.9kg (with stand), 3.1kg (without stand), 5.2kg (packaging)
<b>REGULATIONS</b>		CE, CB, TUV.com, ISO 13406-2 (pixel failure class II), UL, cUL, GOST-R+Hygienic, FCC-B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, MIC, BSMI, PSB, TÜV-S, MPR II, VCCI, CCC, EPEAT, Ukraine, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets ENERGY and ENERGY STAR standards
<b>SECURITY</b>		Kensington® security port
<b>WALL MOUNT</b>		VESA FDMI 100mm x 100mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD-ROM (multi-language User Guides/drivers and SRS WOW HD software)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

**ViewSonic Europe Limited/UK**

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

**ViewSonic Germany**

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Belux**

**ViewSonic Denmark**

**ViewSonic Finland**

**ViewSonic MEA**

**ViewSonic Netherlands**

**ViewSonic Norway**

**ViewSonic Spain**

**ViewSonic Sweden**

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)20 7120 860  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter. <sup>2</sup> Requires SRS Audio Sandbox software to be installed. <sup>3</sup> Some features may not be available on all inputs.