

## Digital media comes to life with the ViewDock™

Stop, Dock and Rock – the ViewSonic 22" VX2245wm ViewDock™ LCD is the ultimate entertainment display. **Dock your iPod®** to access all your digital content. **Boost** your handheld photos and videos and view on the large widescreen display. Hear your digital content with built-in stereo speakers and additional **subwoofer** for unparalleled audio performance – or go silent with the **headphone jack**. Manage your digital media with the integrated **8-in-1 digital card reader** for camera cards. Connect your digital devices through the **4 USB ports**. Chat on-line using the built-in **microphone**. The super-fast 5ms response time screen lets you watch movies or play games free from blurs or ghosting. Your desktop experience will never be the same once you bring it all together with the VX2245wm ViewDock and iPod®!

**IT'S NOT JUST THE ULTIMATE ENTERTAINMENT DISPLAY - IT'S A VIEWSONIC.**

# VX2245wm

**22" WIDESCREEN  
VIEWDOCK™ LCD**

**WITH IPOD® DOCK IN  
MULTIMEDIA BASE**



### MAKE YOUR DESKTOP A DIGITAL MEDIA DESTINATION

- > **Multimedia base with iPod® dock**  
Multimedia base features iPod® dock, 8-in-1 card reader, microphone, headphone jack, 4 USB ports and subwoofer.
- > **Widescreen performance for movies and games**  
Play games and watch movies on the 22" viewable widescreen with 1680 x 1050 resolution.
- > **Enhanced audio performance**  
Built-in stereo speakers and additional integrated subwoofer.
- > **ClearMotiv™ 5ms video response time**  
Super-fast 5ms video response time delivers images free from blurs or ghosting.
- > **Ultra-high brightness and contrast**  
See the Difference with ViewSonic's award-winning screen performance. 700:1 contrast levels and 280cd/m<sup>2</sup> brightness deliver rich, crisp, detailed images.
- > **Stylish slim-bezel design with glossy piano-black finish**  
Gloss piano-black / matt black finish and ultra-modern design for the latest in styling.
- > **OptiSync® digital/analogue inputs expand your connectivity**  
Multi-mode input technology supports both digital and analogue signals for ultimate compatibility and configuration flexibility.
- > **PC and Mac® compatible**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**   
the choice of professionals

# VX2245wm

**ViewSonic**   
the choice of professionals

## 22" WIDESCREEN VIEWDOCK™ LCD WITH IPOD® DOCK IN MULTIMEDIA BASE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

### ViewSonic Europe Limited/UK

ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

### ViewSonic Denmark

### ViewSonic Finland

### ViewSonic Italy

### ViewSonic MEA

### ViewSonic Netherlands

### ViewSonic Norway

### ViewSonic Spain

### ViewSonic Sweden

Tel: +32 (0) 56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0) 9 5406 4070  
Tel: +39 02 73 95 50 22  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0) 20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

|                             |                    |  |
|-----------------------------|--------------------|--|
| <b>LCD</b>                  | Type               | 22" Wide TN colour TFT active matrix WSXGA+ LCD  |
|                             | Display Area       | 47.4cm horizontal x 29.6cm vertical, 55.9cm diagonal   |
|                             | Pixel Pitch        | 0.282mm  |
|                             | Optimum Resolution | 1680 x 1050@60Hz   |
|                             | Pixel Clock        | 150MHz   |
|                             | Contrast Ratio     | 700:1 (typ.)   |
|                             | Viewing Angle      | 150° horizontal, 140° vertical (at 10:1), 170° horizontal, 160° vertical (at 5:1)  |
|                             | Response Time      | 5ms (off-on-off) (typ.)  |
|                             | Colour Support     | 16.2M colours (6-bit+2-bit FRC)  |
|                             | Light Source       | Long life, 40000 hrs. (typ.)   |
|                             | Brightness         | 280cd/m <sup>2</sup>   |
|                             | Panel Surface      | Anti-glare   |
| <b>VIDEO INPUT</b>          | Analogue           | RGB analogue (0.7 Vp-p, 75 ohm)  |
|                             | Digital            | DVI-D (TMDS, 100 ohm)  |
|                             | Frequency          | F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~85Hz  |
|                             | Synchronisation    | H/V separate (TTL), composite, sync on green   |
| <b>COMPATIBILITY</b>        | PC                 | VGA up to 1680 x 1050 non-interlaced   |
|                             | Mac <sup>®2</sup>  | Power Mac™ G3/G4/G5 up to 1680 x 1050 non-interlaced   |
| <b>CONNECTOR</b>            | Analogue           | 15-pin mini D-Sub (detachable cable)   |
|                             | Digital            | 24-pin DVI-D (detachable cable)  |
|                             | ViewDock™          | iPod® dock (Made for iPod® certified)  |
|                             | Audio              | 1 x 3.5mm stereo audio line-in, 1 x 3.5mm stereo audio line-out  |
|                             | Headphone          | 3.5mm mini stereo jack   |
|                             | Card Reader        | 8-in-1 digital card reader   |
|                             | USB                | USB 2.0 hub, 1x upstream (4-pin Typ B)/4x downstream (4-pin Typ A)   |
|                             | Power              | 3-pin AC plug (CEE22) (Display), DC plug (base)  |
| <b>AUDIO</b>                | Speakers           | 2 x 2.5 watt integrated stereo speakers  |
|                             | Subwoofer          | 1 x 3 watt intergrated into base   |
|                             | Microphone         | Integrated into base   |
| <b>POWER</b>                | Voltage            | AC 100~ 240V, 50/60Hz (auto switch), internal power supply (Display)   |
|                             | Consumption        | 62 watt (typ.), <1 watt in power save mode   |
| <b>ERGONOMICS</b>           | Tilt               | Down 5°, Up 20°  |
| <b>CONTROLS</b>             | Basic              | Power, menu [1], up, down, select [2], mute, subwoofer volume up/down  |
|                             | OSD <sup>3</sup>   | Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall |
| <b>OPERATING CONDITIONS</b> | Temperature        | 5°C–35°C   |
|                             | Humidity           | 20%–80% (non-condensation)   |
| <b>DIMENSIONS</b>           | (W x H x D mm)     | 524 x 493 x 212 (with stand)<br>524 x 388 x 58 (without stand)<br>580 x 610 x 260 (packaging)  |
| <b>WEIGHT</b>               | Net                | 6.2kg (with stand)<br>4.8kg (without stand)  |
|                             | Gross              | 8.5kg  |
| <b>REGULATIONS</b>          |                    | CE, CB, NEMKO/ERGO <sup>4</sup> , ISO13406-2 (pixel failure class II), GOST-R + 20 original copies hygienic, UL, cUL, FCC-B, Energy Star®, NOM, MPR II, SASO, BSMI, CCC, PSB, C-TICK, WEEE, RoHS   |
| <b>POWER MANAGEMENT</b>     |                    | Meets MPR II and Energy Star® standards  |
| <b>SECURITY</b>             |                    | Kensington® security port  |
| <b>WALL MOUNT</b>           |                    | VESA FDMI 100mm x 100mm  |
| <b>PACKAGE CONTENT</b>      |                    | LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, audio cable, USB cable, iPod® adapter, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)   |
| <b>WARRANTY</b>             |                    | Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>   |

<sup>1</sup> iPod® must be purchased separately. <sup>2</sup> May require optional Mac adapter. <sup>3</sup> Some features may not available on all inputs. <sup>4</sup> Equivalent to TÜV/ERGO.  
Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX2245wm 12/06-UK