

CD4233

42" SLIM BEZEL FULL HD 1080P COMMERCIAL LCD DISPLAY"

Grand Format for Large, Crisp Digital Signage Images



Overview

ViewSonic's 42" CD4233 Commercial Display is designed for use in educational, retail, public and commercial signage applications. Full 1080p resolution provides a clear view in any installation. Generous screen size and super slim bezel make messages stand out in a big way. Multiple connectivity and resolutions provide you with lots of options for showing a diverse set of digital signage content; from video, to internet pages, PowerPoint, Flash, and much more with ultimate HD clarity. Display your vivid graphics and stunning video beautifully with this large, bright and high contrast screen.

Features

1080p 9ms panel for vibrant video and crisp images

16.3mm slim bezel

Display wall capability up to 5x5

RS-232 daisy-chain capable

VGA and DVI inputs/outputs for flexible connectivity and control

Remote and panel control lock out

7 day on/off scheduling

Screen saver/image sticking protection

Built-in 5Wx2 speaker with 7Wx2 output

Installation options include stand or VESA wall mount

Technical Specifications

LCD	Type	42" color TFT active matrix, wide LCD
	Contrast Ratio	1100:1 (typ)
	Viewing Angles	178° horizontal, 178° vertical
	Brightness	700 cd/m2 (typ)
	Display Area	36.6" horizontal x 20.6" vertical; 42" diagonal
	Optimum Resolution	1920x1080, 600mm dot pitch
	Response Time	9ms
	Light Source	Long life, 50,000 hrs. (typ)
	Aspect Ratio	16:9
	Panel Surface	Anti-glare, hard coating (3H)
DIMENSIONS	Physical Without Stand	38.1" x 22.0" x 4.9" (967.6mm x 559.6mm x 123.1mm)
	Physical with stand (optional)	38.1" x 25.5" x 15.9" (967.6mm x 647.7mm x 403.9mm)
REGULATIONS		FCC, ICES003, UL, cUL, CE, CB, ENERGY STAR®
PACKAGE CONTENTS		LCD display, power cable, remote control with batteries, User Guide CD
AUDIO	Amplifier	7-watt / 8 ohm
INPUT	Video Input	HDMI, DVI, component, VGA, S-Video, composite
	Video Output	VGA, component, DVI
	Control Input/Output	RS-232
CONNECTOR	Digital	HDMI, DVI
	Power	3-pin plug
	Analog	15-pin mini D-sub (VGA)
POWER	Voltage	AC 100-240V (universal), 50-60Hz
	Consumption	280W (typ)
CONTROLS	Picture	Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness
	Front Panel	Power, Exit, +, -, Menu/Enter

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic
See the difference™ 



Special	Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset
Audio	Volume, mute, audio source
Diagnostic	Thermal, back light, ambient, 5V detect, 12 detect
Input	VGA, DVI, HDMI, YPbPr
OSD Setting	Languages, OSD H. position, OSD V. position, OSD timer
VGA Setting	Auto adjustment, clock, phase, sharpness, H. position, V. position

VESA MOUNT COMPLIANT		VESA 100mm x 100mm, 12 holes
WEIGHT	Gross without stand	76.5 lb. (34.7 kg)
	Net With Stand	69.8 lb. (31.7 kg)
	Net Without Stand	65.0 lb. (29.5 kg)
OPERATING CONDITIONS	Humidity	20–80% (non-condensing)
	Temperature (landscape)	41–104°F (5–40°C)
	Temperature (portrait)	41–95°F (5–35°C)
INPUT SIGNAL	Video	480i, 480p, 720p, 1080i, 1080p
RECYCLE/DISPOSAL	The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

