

PJD5112

Light Bright and Portable Projector

120HZ AND 3D READY

Affordable and easy to use

The ViewSonic PJD5112 is a practical projector that offers outstanding value and performance. This SVGA resolution projector supports high definition signals and projects 2700 lumens for clear, bright images in most lighting conditions. At only 2.7kg, it is light and compact, making it ideal for the mobile presenter or to move from room to room in the office or on a campus. Texas Instruments' BrilliantColor. technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5112 is an excellent multifunctional data/video projector. The Eco-mode function reduces fan noise for less distraction during important presentations and even extends the lamp life up to 5000 hours*. The PJD5112 is perfect for users looking for an easy to use, versatile and portable projector at a great price.



Versatile Presentations Anywhere

> BrilliantColor technology

Latest BrilliantColor™ technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

> Bright in virtually any setting

Packs 2,700 ANSI lumens in just 2.7kg, and with a high 2800:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> Eco-mode extends lamp life

Extend the life of your lamp up to 5000 hours* and reduce noise output to a whisper quiet 29dB.

> Off-to-Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

PJD5112

LIGHT, BRIGHT AND PORTABLE PROJECTOR

Model No. VS12618



- >Replacement lampRLC-050
- >Wireless presentation gatewayWPG-350
- >Ceiling mountWMK-018
- >Soft casePJ-CASE-001

Projection	4:3 Screen Screen Size				
	Wide		Tele		
M	feet	m	inch	m	inch
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
1.5	4.92	1.17	46.14	0.99	39



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Type	1.4cm/ 0.55" Digital Micromirror Device(DLP™)
	Resolution	SVGA 800×600(Native) / UXGA 1600×1200(compressed)
	Lens	1.2× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction:+/- 40 degrees
	Display Size(diagonal)	68.5cm/ 27" - 762cm/ 300"
	Throw Distance	1.2m-10m
	Throw Ratio	1.6-1.9
	Lamp	180watt (RLC-050)
	Lamp Life(Normal/ Eco Mode)	3500 / 5000 (hours)
	Brightness	2700 Lumens
	Contrast Ratio	2800:1
	Aspect Ratio	4:3 (native) & 16:9
AUDIO	Speaker	2W ×1
INPUT SIGNAL	Computer and video	NTSC M(3.58MHz), 4.43MHz, PAL(B, D, G, H, I, M, N, 60), SD 480i and 576i(24fps, 25fps and 30fps), ED 480p and 576p(24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh:31-100KHz, Fv:50-120Hz
COMPATIBILITY	PC	VGA to UXGA
	Mac	Up to 1152 × 864 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1 × RS-232 (8 Pin Mini-Din)
	USB	1 × TYPE B (Firmware upgrade)
	Power Output	12V DC Connector
POWER	Voltage	90~240VAC (Auto Switching), 50 / 60Hz (universal)
	Power Consumption	235W (Typical) / <1W (Stand-by mode)
LANGUAGE		English/ Dutch/French/ Spanish/Italian/ Korean/ Thai/ Portuguese/ T. Chinese/ S. Chinese/ Japanese/ Russian / German/ Swedish/ Turkish/ Finnish/ Polish
CONTROLS	Basic	POWER, Keystone/ Arrow keys, Left/ BLANK, MENU/ EXIT, Right/ Panel key lock, AUTO, MODE/ ENTER, SOURCE
	OSD	Picture: Brightness, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync invert. Computer Image: Frequency, tracking, H position, V position. Video Image: Saturation, sharpnes, tint. Setting: Manu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, ECO mode, high altitude, OSD timeout. Advance: Blank screen, password word, screen capture, start up screen, text shot, digital zoom, DCR, close captions, brilliant color.
OPERATING CONDITIONS	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-80% (non-condensing)
	Altitude	0~1800m (6000ft), operational up to 3048m(10,000ft) at reduced reliability and performance
NOISE LEVEL	Normal / Eco Mode	31dB / 29dB
DIMENSIONS (W x H x D)	Physical	280 × 114 × 218 (mm) / 11 × 4.5 × 8.58 (inch)
WEIGHT	Net	2.66kg(5.86 lb)
REGULATIONS		CB, ROHS, WEEE, UL / cUL, FCC-B, ICES-003, NOM, PSB, C-tick, CE, TUV / GOST-R, Hygienic, UKrSEPRO, CCC
	PACKAGE CONTENTS	ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD(with User Guide)

ViewSonic Europe Limited/UK
Tower 42
25 Old Broad Street
London EC2N 1HQ
Tel./fax: +380 44 537 48 47

ViewSonic Germany
ViewSonic Technology GmbH
Koenigstr. 10C
70173 Stuttgart
Phone: +49 (0) 711 222 54 482
Fax: +49 (0) 711 222 54 200

ViewSonic France
5 rue du Helder
75009 Paris
France
Tel: +33 1 53 24 53 97
Fax: +33 1 53 24 53 98

ViewSonic Corporation
381 Brea Canyon Road Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

2010/02/01-V4