

# PJD5152

Show your big ideas with incredible short-throw distance

## PORTABLE SHORT THROW SVGA DLP PROJECTOR WITH BRILLIANTCOLOR™

ViewSonic's mighty PJD5152 sets the stage for a new generation of versatile projectors equipped with BrilliantColor™ technology and an short throw ratio lens producing a 50" image at a distance of only 1 meter away. With its short throw lens, the PJD5152 saves space by allowing you to place it at the front of your table and still display large, crisp images. Weighing in at just 2.5 kg with 2,600 ANSI lumens and a 3000:1 contrast ratio (with DCR), it's easy to give multimedia lessons in the classroom or dynamic presentations in the small meeting rooms as well as in the executive offices. PJD5152 is ideally perfect for small group discussion. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and x1.2 optical zoom ensure the best possible image regardless of location. With up to 6,000 hours of lamp life\*, low cost replacement lamps, filter-less design and a non-degrading DLP® light engine, the PJD5152 is one of the lowest total cost of ownership projectors in the industry.



VIEWSONIC  
PRODUCTS, PROGRAMS,  
AND SERVICES

### Short-throw lens for large, stunning images in small spaces

The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 50" is possible from just 1 meter

### Eco-mode extends lamp life

Extend the life of your lamp up to 6,000 hours\* and reduce noise output.



### Bright in virtually any setting

Packs 2,600 ANSI lumens in just 2.5 kg, and with a high 3000:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

### Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.

### BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

### 3D DLP® Link ready

With the advanced 3D DLP technology, PJD5152 can convert 60Hz video signals from standard DVD players into the amazing 120Hz format.

\*\* Running ECO-mode exclusively can extend lamp life.

**ViewSonic®**  
See the difference™ 

# PJD5152

## PORTABLE SHORT THROW SVGA DLP PROJECTOR WITH BRILLIANTCOLOR™



### Optional Accessories

Replacement Lamp ..... RLC-055  
 Wireless G Presentation Gateway---WPG-360  
 3D goggle ..... PGD-150

Projection Distance		4:3 Screen Size	
M	Inch	M	Inch
0.7	29	1.0	40
1.1	43	1.5	60
1.5	58	2.0	80
2.2	87	3.0	120
3.7	144	5.1	200
4.6	181	6.4	250
5.5	217	7.6	300

Model Name		PJD5152
Display	Type	0.55" Digital Micromirror Device (DLP.)
	Resolution	SVGA 800×600 (Native)
	Lens	Manual zoom / Manual focus
	Keystone	Vertical digital keystone correction: + / - 40 degrees
	Throw Distance	1.2m - 11.3m
	Throw Ratio	0.9-1.08
	Zoom factor	1.2x
	Lamp	220 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000* hours
	Brightness (Maximum)	2600 Lumens
	Contrast Ratio (Typical)	3000:1 (with DCR)
	Colour Depth	24 bits, 16.7M Colours (8+8+8)
	Colour Wheel	6-Seg RGBCYW / 7200rpm
	Colour Gamut	94 % NTSC 1931 CIE
Audio	Speaker	5Wx1
Input Signal	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31-100KHz, Fv: 48-120Hz
Compatibility	PC	VGA to UXGA
	Mac	Up to 1400×1050 (may require Mac Adapter)
Connector	RGB	Input: 2 × 15-pin mini D-sub, Output: 1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (9 Pin Mini-Din)
Power	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Power Consumption	280W (Typical) / <1W (Stand-by mode)
Language		English/ Frence / Germany/ Italian/ Spanish/ Russian/ T. Chinese/ S. Chinese / Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese/ Thai/ Polish/ Finnish
	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock,Power / Freeze/ Blank / Auto / Menu / 4 direction buttons /VGA1 &2 / Video / Source / Enter/ Exit / Keystone+/- / Magnify +/- / Volume +/- / Mute / Colour Mode
Controls	OSD	<b>Display:</b> Screen colour/ Aspect ratio/ Keystone/ Position/ Phase/ H. Size/ Digital Zoom/ 3D sync/ 3D sync invert/ Colour management <b>Picture:</b> Preset ModeBrightest/ Daylight/Game/ ViewMatch/ Cinema/ User 1/ User 2Reference Mode: Brightest/ Daylight/ ViewMatch/ Cinema/GameBrightness /Contrast /Colour /Tint / Sharpness/ Brilliant Colour/Colour Temp. /Save Settings <b>Source:</b> Quick Auto Search/ Language/ Projector Position/ Auto Power Off/ Blank Timer/ Panel Key lock/ Timer Controller /Splash Screen/ Message <b>System Setup (Advanced):</b> Quick Cooling/ High Altitude Mode/ DCR/ Active VGA Out/ Audio Settings/ Menu Settings/ Closed Caption/ Lamp Settings/ Security Setting/ Reset All Settings
	Information	
Operating	Temperature	0°C-40°C
Condition	Humidity	10%-90% (non-condensing)
Noise Level	Normal / Eco Mode	32dB / 26dB
Dimensions	Physical (W×H×D)	264 × 96.4 × 225 (mm)
Weight	Net	2.5 kg
Regulations		CB, UL, cUL, FCC (including ICES-003), CE,UL-Argentina, NOM, TUV-GS, GOST-R,SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS
Packing		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
Contents		



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



For more product information, visit us at [www.viewsoniceurope.com](http://www.viewsoniceurope.com)

See the difference™