

PJD5351

LIGHT, BRIGHT AND VERSATILE DLP PROJECTOR

WITH EXTREME SHORT-THROW LENS

Short distance - big presentation

The powerful PJD5351 sets the stage for a new generation of versatile projectors equipped with BrilliantColor™ technology and an extreme short-throw ratio – producing a 60" image at a distance of only 1.1m away. With its short-throw lens, the PJD5351 saves space by allowing you to place it at the front of your table and still display large, crisp images. Weighing in at just 2.5kg with 2500 ANSI lumens and a 2400:1 contrast ratio (with DCR), it's easy to give multimedia lessons in the classroom or dynamic presentations in the boardroom. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and digital zoom ensure the best possible image regardless of location. With up to 4000 hours of lamp life*, low-cost replacement lamps, filter-less design and a non-degrading DLP® light engine, the PJD5351 has one of the lowest total cost of ownership ratios in the industry.



Versatile presentations anywhere

- > **Short-throw lens for large, stunning images in small spaces**
The short-throw lens enables large images to be projected from short distances in small rooms. A screen size of 1.5m is possible from just 1.1m
- > **Advanced connectivity**
In addition to standard connectors, this projector provides two RGB inputs to easily switch between presenters and an additional RGB output to connect to an external monitor.
- > **Bright in virtually any setting**
Packs 2,500 ANSI lumens in just 2.5kg, and with a high 2400:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.
- > **BrilliantColor™ technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.
- > **Eco-mode extends lamp life**
Extend the life of your lamp up to 4000 hours* and reduce noise output to a whisper quiet 27db.
- > **Off-to-Go feature**
The direct-off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

PJD5351

PORTABLE VERSATILE DLP PROJECTOR

ViewSonic®
See the difference™ 



Optional Accessories

- >Replacement lamp RLC-047
- >Universal ceiling mount kit WMK-018
- >Wireless G presentation gateway WPG-150
- >3 year extended lamp warranty LSWP3

Projection Distance 4:3 Screen		Screen Size (diagonal) 4:3 Screen	
m	feet	m	inch
0.7	2.3	1.0	40
1.1	3.6	1.5	60
1.5	4.9	2.0	80
1.8	5.9	2.5	100
2.8	9.2	3.8	150
3.2	10.6	4.6	180



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
	Lens	Fixed zoom/ manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size (diagonal)	40"-180" / 1.0m - 4.6m
	Throw Distance	0.75 - 3.5m
	Throw Ratio	0.9:1
	Lamp	189 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000 hours*
	Brightness	2500 Lumens
Contrast Ratio	2400:1 (with DCR)	
Aspect Ratio	4:3 (native) & 16:9	
Color Gamut	85 % NTSC 1931 CIE	
AUDIO	Speaker	5Wx1
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 30-100 KHz, Fv: 50-87 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1280x1024 (may require Mac Adapter)
CONNECTOR	RGB Input	2 x 15-pin mini D-sub
	Component	2 x 15-in mini -D-Sub (sharer with RGB)
	RGB Output	1 x 15-pin mini D-sub
	Composite Input	1 x RCA jack
	S-Video Input	1 x 4-pin mini-DIN
	Audio Input	1 x 3.5mm mini jack
	Audio Output	1 x 3.5mm mini jack
	Control	1xRS-232 (8 Pin Mini-Din)
POWER	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	242W (Typical) / <5W (Stand-by mode)
LANGUAGE		English, French , German, Italian, Spanish, Russian, Traditional Chinese, Simplified Chinese, Japanese, Korean, Swedish, Dutch, Turkish, Czech, Portuguese, Thai, Polish, Finnish
CONTROLS	Keypad	Standby/On, input, menu
	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom Picture: Preset mode: brightest, standard (Video) ,daylight, ViewMatch (PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness, BrilliantColor™, color temp., save settings) Source: Quick auto search System setting (Basic): Language , projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System setting (Advanced): Quick cooling, high altitude mode, DCR, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
OPERATING CONDITIONS	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10% - 90% (non-condensing)
	Altitude	0~1,800m (6000ft), operational up to 3,048m (10000ft)
NOISE LEVEL	Normal / Eco Mode	30dB / 26dB
DIMENSIONS (W x H x D)	Physical	264 x 96.4 x 225 (mm) / 10.4 x 3.8 x 8.86 (inch)
		380 x 324 x 191 (mm) / 14.9 x 12.8 x 7.5 (inch)
WEIGHT	Net	2.5 kg (5.5lb)
REGULATIONS		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide), soft case
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp

Rev.1.0

ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Subbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. PJD5351

For more product information, visit us on the web at viewsoniceurope.com