

PJD5352

Portable short throw projector

Small projector. Big presentations

ViewSonic's powerful PJD5352 sets the stage for a new generation of versatile projectors equipped with BrilliantColor™ technology and an extreme short throw ratio – producing a 60" image at a distance of 1.1 metres. With its short throw lens, the PJD5352 saves space by allowing you to place it at the front of your table and still display large, crisp images. Weighing in at just 2.5 kg with 2,600 ANSI lumens and a 3000:1 contrast ratio (with DCR), it's easy to give multimedia lessons in the classroom or dynamic presentations in the boardroom. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and optical zoom ensure the best possible image regardless of location. With up to 6,000 hours of lamp life*, low cost replacement lamps, filter-less design and a non-degrading DLP® light engine, the PJD5352 is one of the lowest total cost of ownership projectors in the industry.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

VERSATILE, IMPACT ANYWHERE



Bright in virtually any setting

Packs 2,600 lumen in just 2.6kg and with a high 3000:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.

Eco-mode extends lamp life

Extend the life of your lamp up to 6,000 hours* and reduce noise output to a whisper quiet 26dB.

BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

Short-throw lens for large, stunning images in small spaces

The short throw lens enables large images to be projected from short distances in small rooms with short throw distances.

3D DLP® Link ready

Supports up to 120Hz frame rate

** Running ECO-mode, exclusively can extend lamp life.

ViewSonic®
See the difference™



PJD5352

Portable short throw projector with brilliantcolor technology



Optional Accessories

Replacement Lamp RLC-055
 Universal Ceiling Mount Kit WMK-005
 Wireless G Presentation Gateway WPG-350

Projection Distance		4:3 Screen Size	
M	Feet	Wide M	Tele Inch
0.7	2.3	1.0-1.2	40-48
1.1	3.6	1.5-1.8	60-72
1.5	4.9	2.0-2.4	80-96
1.8	5.9	2.5-3.0	100-120
2.8	9.2	3.8-4.6	150-180
3.2	10.6	4.6-5.5	180-216

Model Name	PJD5352		
DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)	
	Resolution	XGA 1024x768 (native) / SXGA 1280x1024 (compressed)	
	Lens	1.2x optical zoom / Manual optical focus	
	Keystone	Vertical digital keystone correction: +/- 40 degrees	
	Size	32"-195" / 0.8m-5m	
	Throw Distance	0.5m-3.5m / 1.8ft-11.5ft	
	Throw Ratio	0.9:1-1.08:1	
	Lamp	220W	
	Lamp Life (Normal / Eco-mode)	4000 / 6000* hours	
	Brightness	2600 Lumens	
	Contrast Ratio	2600:1 (typ), 3000:1 (dynamic)	
	Aspect Ratio	4:3 (native) and 16:9	
	INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
Frequency		Fh: 31-100KHz, Fv: 48-120Hz	
COMPATIBILITY		PC	VGA to SXGA
Mac®		Up to 832x624 (may require Mac adapter)	
CONNECTOR		RGB Input	15-pin mini D-sub (x2)
		RGB Output	15-pin mini D-sub
		Component	15-pin mini D-Sub (shared with RGB) (x2)
		Composite Input	RCA jack
		S-video Input	4-pin mini-DIN
		Audio Input	3.5mm mini jack
	Audio Output	3.5mm mini jack	
	Control	RS-232 (8-pin mini-DIN)	
AUDIO	Speaker	5W	
	Amplifier	1W	
POWER	Voltage	100-240VAC (Auto Switching), 50/60Hz (universal)	
	Consumption	280W (typ) / <1W (stand-by mode)	
CONTROLS	Basic	Standby/On, input, menu	
	OSD	Display: Screen color, aspect ratio, keystone position, phase, H. size, digital zoom, 3D sync, 3D sync input Picture: Preset mode (brightness, standard (video), daylight, ViewMatch™ (PC), cinema, user 1/user 2), brightness, contrast, color, tint, sharpness, BrilliantColor™, color temperature, save settings Source: Quick auto search System Setting (Basic): Language, projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System Setting (Advanced): Quick cooling, high altitude mode, dynamic contrast ratio, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)	
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)	
	Humidity	10%-90% (non-condensing)	
	Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3048m)	
NOISE LEVEL	Normal / Eco-mode	32dB / 26dB	
DIMENSIONS	Physical	10.4"×3.8"×8.86" (264mm×96.4mm×225mm)	
	Packaging	15.0"×12.8"×7.5" (380mm×324mm×191mm)	
WEIGHT	Net	5.5 lb. (2.5 kg)	
	Gross	8.8 lb. (4.0 kg)	
REGULATIONS		CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC	
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, soft case, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



For more product information, visit us at www.viewsoniceurope.com