

PJD7383

3D ready professional projector

Short Distance-Big Presentation

The PJD7383 is an advanced ultra short throw DLP® projector which includes BrilliantColor™ technology to produce more vibrant colors, while the high brightness and contrast ratio make this projector shine in virtually any lighting situation.

With its ultra short throw lens, it can project an 81-inch image from just 3 feet. The PJD7383 delivers 3000 lumens, 3000:1 dynamic contrast ratio with a 1024 x 768 XGA native resolution, and has a wide range of input options including dual RGB ports, Ethernet RJ45, USB and WiFi (with optional adapter).

The PJD7383 can be displayed and managed over the network through its advanced management software. The ViewSonic PJD7383 is the ideal projector for both businesses and schools.



BrilliantColor™ Technology

With the implementation of a sophisticated 6-segment color wheel, all-digital projection through BrilliantColor™ DLP Technology depicts images as they are meant to be seen. The amazing performance in sharpness, clarity and color expression brings life before your eyes.

Advanced DLP™ Panel, seamless expression of images

The Optical Engine packs advanced 12" DDR DMD chip to smoothly enhance the color and sharpness of images. Without cell gaps on the screen, sensual and punctual graphics indulges naked eyes for wilder imagination.

Crestron RoomView

Worldwide first Crestron RoomView control with management remote control software system built in.

Short-throw lens for large, stunning images in small spaces

The short throw lens enables large images to be projected from short distances in small. A screen size of 66" is possible from just 1.2m.

Digital Keystone Correction: ±40°, adaptivity in any given environment.

Digital Keystone Correction answers to inevitable image distortion in various environments. The images are instantly squared in correct proportion, what you see is what you get.

USB Type-A Port

In an interactive learning or sharing environment, USB Type-A Port allows users to capture precious moments of debates and discussions into PC or NB devices at any given time.

Off To Go

Allow to unplug projector power cable without traditional turn off procedure.

Network control through RJ45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

Networked Display

Networked Display allows the same video stream to be networked across multiple displays to connect projectors in different classrooms or to network video in digital signage applications.

** Running ECO-mode exclusively can extend lamp life.

ViewSonic®
See the difference™

PJD7383

A New Standard to Meet A Higher Expectation



Optional Accessories

- 3D Goggle PGD-150
- Replacement lamp RLC-057
- Ceiling mount WMK-025
- Wireless dongle WPD-100

Projection Distance		4:3 Screen Screen Size	
M	Feet	Wide	Tele
M	Feet	M	Inch
0.5	1.6	1.0	40
0.7	2.3	1.5	60
1.0	3.3	2.0	80
1.2	3.9	2.5	100
1.5	4.9	3.0	120
1.9	6.2	3.8	150
2.5	8.2	5.1	200
3.1	10.2	6.4	250
3.7	12.1	7.6	300

Model Name	PJD7383	
Display	Type	0.55" Digital Micromirror Device (DLPTM)
	Resolution	XGA 1024 x 768 (Native)
	Lens	Manual Zoom/Manual focus
	Keystone	Vertical digital keystone correction: ± 40 degrees
	Throw Distance	0.37m - 3.7m
	Throw Ratio	0.61
	Lamp	210 watt
	Lamp Life (Normal / Eco Mode)	4000 / 6000 (hours)
	Brightness (Maximum)	3000 Lumens
	Contrast Ratio (Typical)	3000:1
	Colour Depth	24 bits, 16.7M Colors (8+8+8)
	Colour Wheel	6-Seg RGBCYW / 7200rpm
	Colour Gamut	90% NTSC 1931 CIE
	Audio	Speaker
Input Signal	Computer and video	NTSC M (3.58 MHz), 4.43MHz PAL (B, D, G, H, I, M, N, 60) SECAM (B, D, G, K, K1, L) 480i and 576i 480p and 576p 720p, 1080i
	Frequency	Fh: 31-100 KHz, Fv: 48-120 Hz
Compatibility	PC	XGA to UXGA
	Mac	Up to 1400x1050 (may require Mac Adapter)
Connector	RGB	2x15-pin mini D-sub/ 1x15-pin mini D-sub
	Composite Input	1xRCA jack
	S-Video Input	1x4-pin mini-DIN
	Audio Input	1x3.5mm mini jack(Microphone) / RCA x1
	Audio Output	1x3.5mm mini jack
	USB	TYPE A x 1 / TYPE B x 1
	Control	1xRS-232 (9 Pin D-Sub) / RJ45
	DC Output	12V trigger
Power	Voltage	100-240VAC(Auto Switching), 50/60Hz (universal)
	Power Consumption	329W (Typical) / <1W (RGB out disable)
Language		English/ France / Germany/ Italian/ Spanish/ Russian/ T. Chinese/ S. Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese/ Thai/ Polish/ Finnish
Controls	Basic	Power / Freeze/ Blank / Auto / Menu / 4 direction buttons /VGA1 &2 / Video / Source / Enter/ Exit / Keystone+/- / Magnify +/- / Volume +/- / Mute / Color Mode
	OSD	(1) Display:Screen color/ Aspect ratio/ Keystone/ Position/ Phase/ H. Size/ Zoom/ 3D sync/ 3D sync invert/ Color Management (2) Picture:Color Mode PC/Video: Brightest/ PC/ ViewMatch/ Cinema/ User 1 / User 2 Reference Mode: PC/Video: Brightest/ PC/ ViewMatch/ Cinema Brightness /Contrast /Color /Tint / Sharpness / Brilliant Color /Color Temp. /Save Settings (3) Source:Quick Auto Search (4) System Setup (Basic):Language/ Projector Position / Auto Power Off /Blank Timer / Panel Key lock/ Splash Screen / Screen Capture/ Message/ LAN Control Settings/Standby Settings (Microphone/ Active VGA Out/ Active Audio Out) (5) System Setup (Advanced): High Altitude Mode /DCR /Audio Settings (Mute/ Volume/ Microphone Volume)/ Menu Settings / Closed Caption / Lamp Settings / Security Setting / Reset All Settings (6) Information: Current System Status (Source / Color mode /Resolution /Color System Equivalent lamp hour/ MAC address) (7) PointBlank: TBD
Operating	Temperature	0°C-40°C
Condition	Humidity	10%-90% (non-condensing)
Noise Level	Normal / Eco Mode	34dB / 29dB
Dimensions	Physical (WxHxD)	290 mm (W) x 254mm (D) x 126 mm (H)
		11.42" (W) x 10 " (D) x 4.96" (H)
Weight	Net	3.5kg (7.7lb)
Regulations		CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, TUV-GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS
Packing		ViewSonic projector, power cable, VGA cable, remote control, lens cap, quick start guide, ViewSonic DVD wizard, soft case
Warranty		3 years



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

For more product information, visit us at www.viewsoniceurope.com

