

VG2236wm-LED

55cm/21.5" WIDESCREEN LED MONITOR

Planet-friendly. Picture perfect.



- > **Up to 50% energy saving with LED backlight**
Without compromising your viewing quality and has eco-friendly mercury free LED backlight.
- > **Multi-functional base design (360° swivel, rotation and height adjust)**
VESA compliant wall-mount interface and detachable base for ergonomic flexibility with pivot, height, tilt and 360° swivel adjustments.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**
Stereo speakers provide clear and rich sound.
- > **MEGA dynamic contrast ratio at 20,000,000:1**
For true-to-life picture depth and clarity in any room.
- > **Widescreen aspect ratio with 1920x1080 resolution**
The widescreen aspect ratio allows you to view Full HD content in its native format with no stretching or distortion.
- > **Wall mountable design**
100mm x 100mm VESA compliant



Model Name	VG2236wm-LED	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (typical) Dynamic Contrast Ratio Viewing Angle (CR ≥ 10 / CR ≥ 5) Response Time (ms) Pixel Pitch (H×V) Panel Surface Light Source (Hours)	55cm/21.5" wide Colour TFT Active Matrix LCD aspect ratio 1920×1080 250 (typical) 1000:1 20,000,000:1 170° (H), 160° (V) 5 (typical) 0.24825 mm x 0.24825 mm Anti-Glare, Hard coating (3H) 25,000 (min.)
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p) H/V separated (TTL), composite sync-on-green 24–83kHz / 50–75Hz
COMPATIBILITY	PC Mac	VGA up to 1920x1080 Non Interlaced 1920x1080 Non Interlaced
CONNECTOR	Analogue Audio Power	1×15 pin mini D-sub 1 x 3.5 mm 3-pin plug (CEE22)
ERGONOMICS	Tilt Swivel Pivot/Rotation Height Adjustment	20 ~ -5 degrees 360 degrees 90 degrees 0 ~ 135 mm
SPEAKER POWER		2x2W AC 100-240V (Universal); 50/60Hz Consumption (W) Save mode (W) ≤0.1W
CONTROLS	Basic OnView / OSD	[1], [2], power button, Down[▼], Up[▲] Auto Image Adjust, Contrast/Brightness, Input Select, D-SUB, DVI, Colour Adjust, sRGB, 9300K, 7500K, 6500K, 5000K, User Colour [R, G, B], Information Manual Image Adjust, H/V Position, Horizontal Size, Fine Tune, Sharpness, Dynamic Contrast, Aspect ratio, Setup Menu, Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background, OSD Pivot, Auto power off, Memory Recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	0 - 40 (°C) / 32 - 104 (°F) 20 - 90 (%)
DIMENSIONS (WxHxD)	Physical (w/ stand)	521.21mm (W) x 427.41 mm (H) x 239.2mm (D)
WEIGHT	Net (w/ stand)	4.4 Kg (9.7lbs)
REGULATIONS		UL, CUL, FCC-B (ICES), CB, CE, CES-003B, ISO13406-2, TUV/GS/ERGO, TUV-S, NOM, GOST-R, HYGIENIC (20 copies), CCC, BSMI, PSB, C-TICK, MIC(KCC), SASO, WEEE, RoHS, SASO, Ukraine, TCO5.0
WALL MOUNT (mm)	VESA® Mount Compliant	100 × 100