

VX1935wm

**19" WIDE SCREEN LCD
WITH CLEARMOTIV™ 5MS
BROADCAST QUALITY VIDEO**

Elegantly-styled fast wide-screen

ViewSonic's 19" VX1935wm wide-screen monitor sets new standards as an entertainment display. See the difference in gaming action with a super-fast 5ms response time to provide fluid images guaranteed to be free from ghosting or blurs. Marvel at the detail in movies with ultra-high brightness and contrast levels to provide rich, clear, detailed images. Connect with ease through both digital (DVI) and analogue inputs. Enjoy full multimedia entertainment with integrated stereo speakers. Plus the stylish glossy piano-black / matt-black finish ensures the VX1935wm looks great turned on or off.

It's not just a fast wide-screen LCD monitor. It's a ViewSonic.



STYLE AND PERFORMANCE FOR DEMANDING HOME-USERS

- > **Wide-screen performance for entertainment**
Immerse yourself with full wide-screen views for intense gaming action.
- > **Wide-screen performance for movies**
Experience movies in wide-screen format - the 16:10 aspect ratio delivers the ultimate in video performance.
- > **Award-winning performance**
See the Difference with ViewSonic's award-winning screen performance. 700:1 contrast levels and 300cd/m² deliver rich, crisp, detailed images.
- > **Stylish slim-bezel design**
Gloss-piano black / matt-black finish and ultra-modern design for the latest in styling.
- > **ClearMotiv™ 5ms video response time**
Super fast 5ms video response time delivers images free from blurs or ghosting.
- > **OptiSync® digital /analogue inputs for maximum connectivity**
Multi-mode input technology supports both digital and analogue signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**
Built-in stereo speakers deliver high-quality audio performance.
- > **Full 19" wide-screen display with 1440 x 900 resolution**



VX1935wm

19" WIDE-SCREEN LCD WITH CLEARMOTIV™ 5MS BROADCAST QUALITY VIDEO



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	19" Wide TN colour TFT active matrix WXGA LCD
	Display Area	41.0cm horizontal x 25.6cm vertical; 48.3cm diagonal
	Pixel Pitch	0.285mm
	Optimum Resolution	1440 x 900@60Hz
	Pixel Clock	136.5MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	130° horizontal, 120° vertical (at 10:1) 150° horizontal, 140° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 40000 hrs. (min.)
	Brightness	300cd/m ²
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	Fh: 30–82kHz, Fv: 50–85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1440 x 900 non-interlaced
	Mac ^{®1}	Power Mac™ up to 1440 x 900 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 1.5 watt integrated speakers
POWER	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OSD ²	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), audio (volume, mute), ViewMatch [®] colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C–40°C
	Humidity	20%–85% (non-condensation)
DIMENSIONS	(W x H x D mm)	450 x 434 x 210 (with stand) 450 x 341 x 76 (without stand) 545 x 515 x 162 (packaging)
WEIGHT	Net	5.6kg (with stand) 4.7kg (without stand)
	Gross	6.6kg
REGULATIONS		CE, CB, TÜV/Ergo, ISO13406-2 (pixel failure class II), GOST-R+Hygienic, MPR II, SASO, Energy Star, ENERGY, WEEE, RoHS
POWER MANAGEMENT		Meets MPR II and Energy Star [®] standards
SECURITY		Kensington [®] security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, D-sub video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.