EP1032r-T

10.1" Touch Digital Poster











Overview

The ViewSonic EP1032r-T is a 10" multimedia all-in-one interactive digital ePoster. It delivers eye-catching touch-interactive commercial messaging at retail POS, hotel lobbies and front desks, conference and exhibition venues, and other high-visibility locations. The EP1032r-T features wireless b/g/n network and LAN connectivity for easy loading of content, and supports Power over Ethernet (PoE) for convenient one-wire installation. Multi-touch compatibility with HTML5 and SMIL formats delivers a 2-way interactive platform for dynamic, customized content. Its built-in media player, 4GB internal storage, and integrated speakers enable the playback of video clips, as well as photos and music, from a USB hard drive or SD/SDHC memory card. Bundled with Signage Manager Express software, the EP1032r-T effectively delivers customized messaging to target audiences. With VESA-mount compliance, the EP1032r-T is installation-ready for any high-visibility, high-traffic location.

Perfect size for up-close, high-impact messaging

ViewSonic's EP1032r-T all-in-one e-poster has a 10.1" display area with 1280 x 800 screen resolution. With its compact design, the EP1032r-T can be deployed anywhere, including retail shelf edges, hotel front desks, in meeting rooms, or on classroom doors. The EP1032r-T features 300-nit brightness and a 500:1 contrast ratio to deliver high-impact, quality messaging that will attract the attention of passersby.







Interactive on-demand messaging for your customers

The EP1032r-T delivers on-demand advertising and messaging while increasing two-way communication with customers. With multi-touch capability, the EP1032r-T is the perfect e-catalog display solution for shelf edges, retail counters and information kiosks in high-traffic venues.









Convenient one-wire installation via Power over Ethernet

The EP1032r-T utilizes state-of-the-art Power over Ethernet (PoE) technology for one-wire installation. This allows you to easily power and connect your displays with just a single cable. PoE also allows you to create multi-display digital signage installations, while reducing installation costs.





Easy loading of content through Wireless/ RJ45 Ethernet

The EP1032r-T integrates wireless 802.11 b/g/n network and RJ45 Ethernet connectivity, providing a convenient and efficient way to load content from a



Support for dynamic W3C/SMIL-format presentations

With the bundled Signage Manager Express software, the EP1032r-T can display W3C HTML5 and SMIL content retrieved from the Internet. This

For more product information, visit us at www.viewsoniceurope.com





PC or laptop connection. Wireless/LAN connectivity can also be used to remotely load content to multiple displays.



content management and scheduling system offers the flexibility to display fresh and interesting content such as news, weather information, stock market trends, sports scores, social networking, or RSS feeds on multiple screens.





4GB of internal memory and SD/SDHC card slot



The EP1032r-T is capable of storing and playing hours and hours of high-definition multimedia content thanks to its 4GB of built-in, shock-resistant, solid-state memory. This reliable all-in-one e-poster will display dynamic content with no crashes, freezes or lost content.





Built-in speakers that really speak to your audience

Integrated with a pair of stereo 2W speakers, the EP1032r-T combines eye-catching multimedia content with high-quality sound effects—creating an incredible audio-visual impression on your target audience.



Built-in media player for creative content playback

With all-in-one functionality, the EP1032r-T has a built-in media player—making the sharing of vivid retail messaging a breeze. The integrated media

Content management and Signage Manager Express software

Great for all venues and scenarios, the bundled Signage Manager Express software lets users transfer multimedia content onto the EP1032r-T from

For more product information, visit us at www.viewsoniceurope.com





player supports photo-with-music playback, as well as 1080p video playback for eye-catching multimedia campaigns and content.

PCs and laptops. This embedded content management tool also lets you format, schedule, and save playback settings.





Technical Specifications

LCD	Size	10.1" viewable
	Туре	TFT LCD Module with LED Backlight
	Display Area	216.96(W) x 135.6(H)
	Optimum Resolution	1280 x 800
	Contrast Ratio	700:1 (typ.)
	Brightness	300 cd/m2
	Viewing Angles	Top 75°/ Bottom 70°/ Left 75° / Right 75°
	Response Time	25ms
	Colour Support	16.7M colors
	Backlight	LED
COMPATIBILITY	HDMI	720p@50/60, 1080i@50/60, 1080p@50/60
CONNECTOR	Audio	x1
	HDMI (input)	x1
	LAN	x1
	SD	x1 (for expand storage)
	Speaker	2-watt x2
CONTROLS	Physical	Touch button
POWER	Voltage	100-240VAC +/- 10% Wide Range
DIMENSIONS	Physical (WxHxD)	10.94 x 7.32 x 1.57 (inches)/ 278 x 186 x 40 (mm)

For more product information, visit us at www.viewsoniceurope.com



WEIGHT	Net	1.72 (lbs)/ 0.78 (kg)
	Gross	3.64 (lbs)/ 1.65 (kg)
REGULATIONS		FCC, CE
PACKAGE CONTENTS		1. AC Adapter
		2. Ethernet Cable
		3. Standard 3.5mm to RCA AC cable
		4. Display stand and screws
		5. Hardware Quick Start Guide
		6. Software Quick Start Guide
		7. Documentation CD
		*Actual content may differ from market to market
VESA® MOUNT		75 x 75mm
OPERATING		
CONDITIONS	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	Operating: 5% ~ 85% @ 40°C, non-condensing
	Altitude	<2000M
	, utado	\2000!!!
WARRANTY		1-year limited
		**Warranty offered may differ from market to market
Input	USB Type A	x 2 (for content loading, F/W upgrade, Key board, Mouse)
	USB Type B (mouse control)	x 1 (for F/W troubleshooting)
STORAGE /		
SHIPPING CONDITION	Temperature	-4°F to 140°F (-20°C to 60°C)
	Humidity	5% ~ 85% non-condensing
	•	-
	Altitude	<2000M
POWER SAVING		
POWER SAVING FUNCTION	On	Max. : 12W

ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

